

Tariff Notice No. 1982/201—Applications for Variation of Exclusion from Approval

NOTICE is hereby given that applications have been made for variations of current exclusion from approval of the Minister of Customs and for admission of such goods as the rates of duty prescribed under the substantive Tariff item therefor:

Port	Appn. No.	Tariff Item	Goods	Rates of Duty		Part II Ref.	Concession Code	Effective	
				Normal	Pref.			From	To
		84. 61. 021	<p>CURRENT EXCLUSIONS: Cocks and valves:</p> <p>EXCLUDING: (NOTE: This approval does not cover taps, bibcocks, fire hydrants, water plumbing fittings, e.g., faucets, shower fittings, bidet fittings, hand basin fittings, toilet fittings)</p> <p>(2) Valves, gate of the following types; (a) Stainless steel 76 mm to 458 mm (3 in. to 18 in.) or; cast iron 76 mm to 356 mm (3 in. to 14 in.) specifically designed for use with pulp or paper stock (b) Brass 6 mm ($\frac{1}{4}$ in.) 9 mm ($\frac{3}{8}$ in.) 12 mm ($\frac{1}{2}$ in.), 19 mm ($\frac{3}{4}$ in.) and 25 mm (1 in.) (c) 6 mm to 102 mm ($\frac{1}{4}$ in. to 4 in.) of any kind of bronze (d) Flanged, cast iron, to B.S. 3464, other than outside screw and yoke types, sizes 51 mm (2 in.), 63.5 mm ($2\frac{1}{2}$ in.), 76 mm (3 in.), 150 mm (6 in.), 200 mm (8 in.) (e) Flanged, cast iron, to B.S. 3464, with indicators, sizes 76 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.), 200 mm (8 in.)</p> <p>(3)—(14)</p> <p>(15) Pressure reducing; (a) Valves of bronze, pilot operated, flanged and screwed, stainless steel seat and valve, sizes 12 mm to 51 mm ($\frac{1}{2}$ in. to 2 in.) up to 172 kPa (250 p.s.i.) (b) Valves of bronze, for water, 12 mm to 25 mm ($\frac{1}{2}$ in. to 1 in.) screwed ends up to 1725 kPa (250 p.s.i.)</p>	Free			202740C	1/3/80	30/6/86
DN	605	84. 61. 021	<p>REQUESTED EXCLUSIONS: Cocks and valves: EXCLUDING: (NOTE: This approval does not cover taps, bibcocks, fire hydrants, water plumbing fittings, e.g., faucets, shower fittings, bidet fittings, hand basin fittings, toilet fittings)</p> <p>(2) Valves, gate, of the following types; (a) Stainless steel 76 mm to 458 mm (3 in. to 18 in.) or; cast iron 76 mm to 356 mm (3 in. to 14 in.) specifically designed for use with pulp or paper stock (b) Brass 6 mm ($\frac{1}{4}$ in.), 9 mm ($\frac{3}{8}$ in.), 12 mm ($\frac{1}{2}$ in.), 19 mm ($\frac{3}{4}$ in.) and 25 mm (1 in.) (c) 6 mm to 102 mm ($\frac{1}{4}$ in. to 4 in.) of any kind of bronze or brass (d) Flanged, cast iron, to B.S. 3464, other than outside screw and yoke types, sizes 51 mm (2 in.), 63.5 mm ($2\frac{1}{2}$ in.) 76 mm (3 in.), 150 mm (6 in.), 200 mm (8 in.) (e) Flanged, cast iron, to B.S. 3464, with indicators, sizes 76 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.) 200 mm (8 in.)</p>						