THE NEW ZEALAND GAZETTE

TARIFF DECISION LIST No. 591—continued

APPROVALS—continued

_	Tariff Item No.		Rates of Duty		Part		Effective	
Port		Goods	Normal	Pref.	II Ref.	cession Code	From	To*
WN	59.17.039	Walker's Stern Gland Packings, Sturntite No.330, Rapido 374,	Free	Free	15	922779C	4/82	3/85
	Chapter 60	H.S. Sturntite 331, Sextant, Glengarry Babies' and young infants' clothing of kinds and sizes, as may be approved by the Minister; APPROVED:	Free	Free	99			
НО		TUNIC SUITS - SMOCK TYPE Knitted outfit incorporating tunic or smock type top and short or full length trousers designed as a set with a maximum length of 41cm*				206849E	11/82	3/84
DN	<0.0< 000	*Length to be measured from point where shoulder joins neck to lowest point on the hem of the garment at the back. Turn-up is to be taken into account when determining maximum length	F	F	1.5	204657B	7,00	0.49.5
DN		Knitted or crocheted rubberised fabric with synthetic or rayon pile mixture, peculiar for use in making paint rollers only	Free	Free	15 99	204657B	7/80	9/85
	Chapter of	Babies' and young infants' clothing of kinds and sizes, as may be approved by the Minister; APPROVED:	Free	Free	99			
НО		TUNIC SUITS - SMOCK TYPE Woven outfit incorporating tunic or smock type top and short or full length trousers designed as a set with a maximum length of 41cm*				206850J	11/82	3/84
но	70.07.009	*Length to be measured from point where shoulder joins neck to lowest point on the hem of the garment at the back. Turn-up is to be taken into account when determining maximum length Ceramic glass panels, on declaration for use in making solid	Free	Free	15	206863L	7/87	6/84
WN	70.20.071	Woven reinforced fabrics, for use in filtering molten aluminium	Free	Free	99	922782C	9/82	9/85
CH DN	73.15.149 73.18.009	Alloy stainless steel wire, lighter than 1.00mm diameter	Free	Free Aul Free	99	909091G 204145G	4/82	3/85
WN	76.02.001	Aluminium wire, American alloy specification 5056, tensile strength 44,000 to 52,000 p.s.i., for use in making tipper tie clips	Free	Free	15	922783A	8/82	
DN	76.04.001	Aluminium foil EXCLUDING:	Free			201954L	10/78	9/85
		(1) 0.013mm to 0.20mm thickness (2) Self-adhesive						
DN	76.04.001	Aluminium foil, backed with bleached kraft and treated with a classified release agent	Free		••	110017D	8/78	9/85
DN	76.06.000	Aluminium tube in bar lengths to metric bore sizes and wall thicknesses, peculiar for use in making compressed air cylinders for industrial automation, sizes 32mm x 2.0mm, 50mm x 2.5mm, 63mm x 2.5mm and 3mm, 80mm x 2.5mm and 3mm and 100mm x 2.5mm and 3mm	Free	Free	15	202981C	7/80	9/85
DN	82.05.019	Ear tap applicator guide pins	Free	Free	15	922784K 204250K		12/84
DN DN	83.05.009	Tungsten carbide inserted guillotine blades Clipboard mechanisms	Free Free	Free Free		110335A	7/78	9/85
WN	84.03.000 84.06.021	GSIL nitrogen generator Watercooled engines, as may be approved; APPROVED:	Free Free	Free	10 	922754H 205280G	10/81	6/85 12/83
		An engine for which the original engine manufacturer obtains a certificate certifying it as complying with a national Standard Specification, internationally acceptable, and attaining its maximum continuous shaft kilowatt rating under either DIN6270						
		(rating A) or BS649;1958 or SAE J816a, at an engine speed not exceeding 2000 rpm.						
		An engine for which the original engine manufacturer obtains a certificate certifying it as complying with a national Standard						
		Specification, internationally acceptable and attaining its maximum continuous shaft kilowatt rating at an engine speed						
		exceeding 2000 rpm under DIN 6270 (rating A) or BS 649; 1958 or SAE J816a, provided that the maximum continuous shaft kilowatt						
CH		rating is greater than 149 shaft kilowatts (200 shaft horsepower) M.A.N. diesel engines;						
WN	84.08.011	D2540MTE Martonair impact cylinders	Free	Free		202746B	2/79	
WN	84.08.011	Martonair positional controllers M1525, M1540, M1830, M1832, M1834, M1840, M1500	Free	Free	10	113137A	3/81	•
WN AK	84.08.011 84.10.029	Hypro centrifugal pumps for use with agricultural tractors,	Free Free	Free Free	10 10	900554E 919995A	10/79 8/82	9/86 6/85
WN	84.10.029		Free	Free	10	922778E	11/82	12/85
DN	84.11.061	declared for use only in agricultural or industrial applications Riello oil and gas burner rotors at 64 CFM at 100mm W.G. static pressure, 144 CFM and 150mm W.G. static pressure and 240 CFM at	Free			202620B	4/80	9/85
DN	84.18.039	200mm W.G. static pressure Petrol filters, assemblies for, consisting of bowls, bails,	Free	Free	10	200339C	7/78	9/85
		screens, strainers and seats Seitz Tirax automatic filler and sealer, for bottling and	Free	Free		919986B		9/85