

## Tariff Notice No. 1983/132—Applications for Variation of Approval

NOTICE is hereby given that applications have been made for variation of current approvals of the Minister of Customs as follows:

Port	Appn. No.	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Con-cession Code	Effective	
				Normal	Pref.			From	To*
			CURRENT APPROVAL: Fittings, mechanisms and metals for loose leaf binders and files EXCLUDING 2 ring 'O' 'D' and square shape fittings between 23 mm and 40 mm capacity, 3 ring 'O' 'D' and square pull open fittings between 23 mm and 40 mm capacity, with rings at 108 mm centres	Free	Free	15	110324F	3/79	6/85
WN	3086	83.05.009	REQUESTED APPROVAL: Fittings, mechanisms, and metals for loose leaf binders and files EXCLUDING 2 ring 'O' 'D' and square shape fittings between 23 mm and 40 mm capacity, 3 ring 'O' 'D' and square pull open fittings between 23 mm and 40 mm capacity, with rings at 108 mm centres, when declared by the manufacturer for use only in the making of loose leaf binders and files						
		83.09.031	CURRENT APPROVAL: Rivets, of kinds approved by the Minister Gesipa blind mechanical rivets up to 100 mm in length	Free			110391B	7/78	6/84
WN	3112	83.09.031	REQUESTED APPROVAL: Gesipa blind mechanical rivets over 57.9 mm in length						
		84.63.029	CURRENT APPROVAL: Crowned and barrelled teeth gear couplings	Free	Free	10	916917C	3/81	6/84
WN	3136	84.63.029	REQUESTED APPROVAL: Crowned and barrelled teeth gear couplings with a rating exceeding 235 kw per 100 rpm only						
		84.63.029	CURRENT APPROVAL: Falk couplings, types 456L, 70GL, and 10F	Free	Free	10	917441K	8/82	9/86
WN	3136	84.63.029	REQUESTED APPROVAL: Falk couplings, types 456L, 70GL, and 10F with a rating exceeding 235 kw per 100 rpm only						
		84.63.029	CURRENT APPROVAL: Holset flexible rubber block couplings	Free	Free	10	919603L	8/82	6/85
WN	3136	84.63.029	REQUESTED APPROVAL: Holset flexible rubber block couplings with a rating exceeding 235 kw per 100 rpm only						
		84.63.029	CURRENT APPROVAL: Hydraulic or fluid couplings for use in transmission between revolving shafts	Free	Free	10	916911D	7/81	6/88
WN	3136	82.63.029	REQUESTED APPROVAL: Hydraulic or fluid couplings for use in transmission between revolving shafts with a rating exceeding 235 kw per 100 rpm						
		84.63.029	CURRENT APPROVAL: Renold internal gear couplings: MB type, series 7071, 2, 3, 4, 7, only, NTS type, series 7078 only	Free	Free	10	204156B	7/80	9/85
WN	3136	84.63.029	REQUESTED APPROVAL: Renold internal gear couplings: MB type, series 7071, 2, 3, 4, 7, only, NTS type, series 7078 only with a rating exceeding 235 kW per 100 rpm						
		84.63.029	CURRENT APPROVAL: Roller chain flexible couplings	Free	Free	10	113085E	1/80	9/85
WN	3136	84.63.029	EXCLUDING: 20 tooth units with chain pitch from 9.5 mm up to and including 25.4 mm						
		84.63.029	REQUESTED APPROVAL: Roller chain flexible couplings EXCLUDING: 20 tooth units with chain pitch from 9.5 mm up to and including 25.4 mm with a rating exceeding 235 kW per 100 rpm						
		84.63.029	CURRENT APPROVAL: Tschan flexible couplings	Free	Free	10	920762H	2/83	6/85
WN	3136	84.63.029	REQUESTED APPROVAL: Tschan flexible couplings with a rating exceeding 235 kW per 100 rpm						
			CURRENT APPROVAL:						