## THE NEW ZEALAND GAZETTE

## TARIFF DECISION LIST No. 649—continued

DETERMINATIONS—continued

	DETERMINATIONS—continued  Rates of Duty Part Con- Effective							
Port	Tariff Item No.	Goods		T	Part II	cession	Effect	
	L		Normal		Ref.	Code	From	To*
	90.28.001 Deter'n	Moving iron ammeters and voltmeters, flush mounting, quadrant scale, to accuracy class 1.5 and having face sizes from 72 mm to 144 mm square Moving coil and moving coil/rectifier ammeters and voltmeters, flush mounting, having face areas of between 5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales NOTE: circular, sector, and quadrant type scales are illustrated in Fig. 2 on pages 11 and 12 of B.S. 3693, PART 1, 1964, "The Design of Scales and Indexes"	45	Aul 15 Can 25 DC 25 Pac Free		208323L	1/84	12/84
	90.28.001 Deter'n	Moving iron ammeters and voltmeters, flush mounting, quadrant scale, to accuracy class 1.5, and having face sizes from 72 mm to 144 mm square Moving coil and moving coil/rectifier ammeters and voltmeters, flush mounting, having face areas of between 5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales NOTE: circular, sector, and quadrant type scales are illustrated in Fig. 2 on pages 11 and 12 of B.S. 3693, PART 1, 1964, "The Design of Scales and Indexes"	45	Aul 10 Can 25 DC 25 Pac Free	• •	208324J	1/85	12/85
	90.28.001 Deter'n	Moving iron ammeters and voltmeters, flush mounting, quadrant scale, to accuracy class 1.5 and having face sizes from 72 mm to 144 mm square Moving coil and moving coil/rectifier ammeters and voltmeters, flush mounting, having face areas of between 5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales NOTE: circular, sector, and quadrant type scales are illustrated in Fig. 2 on pages 11 and 12 of B.S. 3693, PART 1, 1964, "The Design of Scales and Indexes"	45	Aul 5 Can 25 DC 25 Pac Free	••	208325G	1/86	12/86
	90.28.001 Deter'n	Moving iron ammeters and voltmeters, flush mounting, quadrant scale, to accuracy class 1.5 and having face sizes from 72 mm to 144 mm square Moving coil and moving coil/rectifier ammeters and voltmeters, flush mounting, having face areas of between 5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales NOTE: circular, sector, and quadrant type scales are illustrated in Fig. 2 on pages 11 and 12 of B.S. 3693, PART 1, 1964, "The		Aul Free Can 25 DC 25 Pac Free	••	208326E	1/87	
но	90.28.001 Deter'n	Design of Scales and Indexes" Portable electrically powered gas leak detector, gas detector and gas monitor and smoke warning alarms	45	Aul 20 Can 25 DC 25 Pac Free	••	208327C	1/83	12/83
	90.28.001 Deter'n	Portable electrically powered gas leak detector, gas detector and gas monitor and smoke warning alarms	45	Aul 15 Can 25 DC 25 Pac Free	••	208328C	1/84	12/84
	90.28.001 Deter'n	Portable electrically powered gas leak detector, gas detector and gas monitor and smoke warning alarms	45	Aul 10 Can 25 DC 25 Pac Free	••	208329K	1/85	12/85
	90.28.001 Deter'n	Portable electrically powered gas leak detector, gas detector and gas monitor and smoke warning alarms	45	Aul 5 Can 25 DC 25 Pac Free	••	208341J	1/86	12/86
	90.28.001 Deter'n	Portable electrically powered gas leak detector, gas detector and gas monitor and smoke warning alarms	45	Aul Free Can 25 DC 25 Pac Free		208342G	1/87	
НО	90.28.001 Deter'n	Post payment self-service petrol dispensing systems	45	Aul 20 Can 25 DC 25 Pac Free		208343E	1/83	12/83
	90.28.001 Deter'n	Post payment self-service petrol dispensing systems	45	Aul 15 Can 25 DC 25 Pac Free	••	208344C	1/84	12/84
	90.28.001 Deter'n	Post payment self-service petrol dispensing systems	45	Aul 10 Can 25 DC 25 Pac Free		208345A	1/85	12/85
	90.28.001 Deter'n	Post payment self-service petrol dispensing systems	45	Aul 5 Can 25 DC 25	••	208346K	1/86	12/86
ă.	90.28.001 Deter'n	Post payment self-service petrol dispensing systems	45	Pac Free Aul Free Can 25 DC 25		208347H	1/87	••
НО	90.28.001 Deter'n	Power factor correction systems, including power factor controllers and ancillary equipment mounted in a common cubicle and designed to measure and automatically control the overall power factor in a 3-phase electrical installation, and such power factor controllers when imported separately	45	Pac Free Aul 20 Can 25 DC 25 Pac Free		208349D	1/83	12/83