

Tariff Notice No. 1983/181—Applications for Variation of Approval—continued

Port	Appn. No.	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Con-cession Code	Effective	
				Normal	Pref.			From	To
		84.25.049	Hesston rotary mower/conditioner 1180	Free	Free	10	207647A	1/83	9/85
H.O.	1951	84:25.049	REQUESTED APPROVAL: Hesston rotary mower/conditioner 1180 EXCLUDING: (1) Parts of general use (2) Power take-off shafts (drive shafts) made up or in kit form CURRENT APPROVAL:						
		84.25.049	Taurup; SKT 2150 straw or maize, cutter/spreader	Free	Free	10	207651K	1/83	9/85
H.O.	1951	84.25.049	REQUESTED APPROVAL: Taurup; SKT 2150 straw or maize cutter/spreader EXCLUDING: (1) Parts of general use (2) Power take-off shafts (drive shafts) made up or in kit form CURRENT APPROVAL:						
		84.25.049	Vicon; KM 240 mower crimper	Free	Free	10	207655B	1/83	6/84
H.O.	1951	84.25.049	REQUESTED APPROVAL: Vicon; KM 240 mower crimper EXCLUDING: (1) Parts of general use (2) Power take-off shafts (drive shafts) made up or in kit form CURRENT APPROVAL:						
		85.23	Winding wire or winding strip of solid or built-up shapes, being insulated with lacquer or enamel to a maximum wall thickness of 0.25 mm and/or insulated with paper, cotton, glass or fibrous material applied helically	5	Aul Free DC Free	..	206662K	7/82	6/84
AK	23804	85.23	REQUESTED APPROVAL: Winding wire or winding strip of solid or built-up shapes, being insulated with lacquer or enamel to a maximum wall thickness of 0.25 mm and/or insulated with cotton, glass or fibrous material applied helically, excluding paper, Nomex and Kapton insulation CURRENT APPROVAL:						
		90.28.009	Electrical measuring, checking, analysing or automatically controlling instruments and apparatus Other; EXCLUDING: (1)-(4) (5) Moving coil and moving coil/rectifier ammeters and voltmeters, including microammeters, milliameters and D.C. millivoltmeters for use with external shunts, flush mounting horizontal sector scales, accuracy class 2.5 and having body diameter of between 54 and 70 mm, except any such instruments having taut band suspension (6) Moving coil and moving coil/rectifier ammeters and voltmeters, including milliameters and D.C. millivoltmeters, for use with external shunts, flush mounting with circular scales accuracy class 1.5 and having face size 96 mm square, except any such instruments having taut band suspension (7) Moving iron ammeters and voltmeters including milliameters, flush mounting and quadrant scales to accuracy class 1.5 and having face size from 72 mm to 144 mm square inclusive, except any such instruments having taut band suspension (8)-(10)	Free	Free	99	201943E	7/78	6/85
H.O.	WN	90.28.009	REQUESTED APPROVAL: Electrical measuring, checking, analysing or automatically controlling instruments and apparatus Other; EXCLUDING: (1)-(4) (5) Moving coil and moving coil/rectifier ammeters and voltmeters, including microammeters, milliameters and D.C.						