THE NEW ZEALAND GAZETTE

No. 202

Tariff Notice No. 1983/229-Applications for Withdrawal of Approval-continued

Tariff Item No.	Goods	Rates of Duty		Part	Con-	Effective	
		Normal	Pref.	II Ref.	cession Code	From	То
85.23.021	Alpha flat ribbon cable	Free			114213F	9/78	3/80
85.23.021	Aluminium braided heater cable	Free		• • •	114214D	7/78	3/84
85.23.021 85.23.021	Ambient heater cable ASEA P.V.C. covered extra flexible cable type RKKR 4	Free Free		••	200174J 114215B	7/79 7/78	9/84 3/84
85.25.021	$core \times 0.25 \text{ mm}^2$ (0.004 sq. in.) and type RKKR	Tice		••	1142150	1/10	5/ 8-
85.23.021	12 core \times 0.25 mm ² (0.0004 sq. in.) ASEA P.V.C. covered extra flexible cable type RKKR of 10 core \times 1.5 mm ² (0.000 cg. in.)	Free		••	114216L	7/78	3/84
85.23.021	19 core \times 1.5 mm ² (0.002 sq. in.) ASEA P.V.C. covered, extra flexible metal braid, screened control cable, type RKKR, 4 core 1 mm	Free		• • •	203165F	6/80	6/84
85.23.021	ASEA P.V.C. covered single core cable, tinned conductor of copper, rated voltage 0.5 mm ² , 250V, 0.75 mm ² ; 400V,	Free		••	114217J	7/78	3/84
85.23.021	1-2.5 mm ² ; 700V Burton cables, P.V.C. cables with tinned copper conduc- tor, for use up to 105°C, approved for use in making elec-	Free		••	204013B	7/80	9/8
85.23.021	tric dishwashers and freezers Cables with specialised fittings attached, when declared by an importer for use only with medical and scientific	Free		••	114222E	7/78	9/84
85.23.021	equipment Cables with specialised fittings attached, when declared by an importer for use only with medical and scientific	Free		••	11422E	7/78	9/84
85.23.021	equipment Conductive thermoplastic screened microphone cable	Free			918326E	9/81	9/84
85.23.021	Dayflex electrical connections, for making anti-sag coiled, electrical truck and trailer connections	Free		••	917772J	11/81	9/84
85.23.021	Earth bonding strand for oil filled cables	Free		• • •	114223C	7/78	9/90
85.23.021	E-flex co-axial cable	Free		••	205262J	8/80	6/84
85.23.021	Elastomeric flexible cords 300/500 volts, VR insulated, PCB sheathed	Free		•••	114224A	8/78	3/8
85.23.021	Electric cable, lead sheathed, with covering of white P.V.C., type EKKL or FKKL, 750 volt	Free		••	114225K	7/78	3/8:
85.23.021	Electronic wrapping wire	Free		••	114226H	7/78	9/80
85.23.021 85.23.021	Elevator trailing cable, multi-core type Esco insulated electric cable fitted with moulded connec-	Free Free		••	114227F 114228D	7/78 7/78	6/84 9/84
85.23.021	tors and receptable terminals of brass Fischer and Porter signal cable	Free			114229B	9/79	9/8
85.23.021	Fixed pitch ribbon cables for making audio equipment	Free		•••	922243L	1/83	6/8
85.23.021	Flexible twin screened cables, types:	Free		•••		•	
	Permaniod M250, M251 Leon Drahtwerke Li 2Y (c) (Y)				114230F 114231D	7/78 7/78	3/84 3/84
85.23.021	Fusible link cable	Free			900913C	8/81	9/8
85.23.021·	Fusible link cable	Free		• • • •	206522D	8/81	9/84
85.23.021 85.23.021	Gas insulated electric power cable, 33 kV Glass fibre insulated 300/300 volt resistant flexible cords,	Free Free		•••	900765C 114233L	10/80 7/78	9/90 6/85
	16/0.20 mm, 24/0.20 mm, and 32/0.20 mm			••			
85.23.021	Greengate welding cable to BS638 with Butyl insulation and niplas sheath	Free		••	201223F	2/80	6/84
85.23.021	Heavily P.V.C. insulated multi-strand, extra flexible, sin- gle core cables, with tinned conductor of copper, maxi- mum 750 V, for installations where atmospheric contemportion aviant arises from 2.5 mm ² to 150 mm ²	Free		• • •	205373L	6/81	9/8:
85.23.021	contamination exists, sizes from 2.5 mm ² to 150 mm ² Helical cable, single conductor coiled cable, sheathed with black P.V.C.	Free		••	206521F	2/81	6/84
85.23.021	High voltage and temperature fibreglass covered wire (complying to L. standard 1010 subject 758) conductor—	Free		••	114234J	7/78	9/80
	 13/0.18 mm, insulation—H.T. vinyl chloride (120°C 3 kV) overall diameter—2 mm, when declared: (a) by manufacturer for use by him only in making colour television receivers; or (b) by an importer for sale by him only to a manufacturer 						
85.23.021	for use by him only in making colour television receivers High voltage 10 kV wire complying with UL standard, 35688 subject 758, conductor 13/0.18 mm, insulation non- flammable polyethylene covering fusible vinyl chloride,	Free		••	114235G	7/78	9/80
85.23.021	diameter 3.1 mm Hitachi flat cable	Free			922761L	7/82	6/8:
85.23.021	Interconnecting/communication cable for IBM machines made of multiple strand insulated wires, grouped together within a cable with a fire retardent P.V.C. cover, viz: Identification part Nos. of cables;	Free		••			
	5578477				201039K	2/80	6/8
85.23.021	5578498 Interconnecting/communication cable for IBM machines, peculiar to use for the transmission of electrical current between two or more units of an automatic data pro-	Free			201040C 114236E	2/80 11/79	6/8: 9/80
85.23.021	cessing system Krautkramer/Branson ultra-sonic testing instrument cables	Free			114237C	7/78	9/83
85.23.021	M-801 cable peculiar to use in Toshafax stencil cutter	Free		••	114237C	7/78	6/8
85.23.021	Mogami playback cable, type 2311, for use in the con-	Free .			922300C	5/83	4/8