## THE NEW ZEALAND GAZETTE

## TARIFF DECISION LIST No. 611

No. 28

Decisions of the Minister of Customs Under the Customs Tariff (Subject to Amendment or Cancellation by Notification in the Gazette) APPROVALS

	5		APPROVALS						
Port	Tariff Item No.	Goods		Rates of Duty		Part		Effective	
				Normal	Pref.	Ref.	cession Code	From	To*
НО	40.11.001	Pneumatic tyres, tyre cases, and tub the following sizes or their equivale ply rating, speed rating, tread-type, or constituent materials); EXPLANTORY NOTES: (1) Sizes have been listed in order f largest in their respective series (2) Bias and radial tyres are shown respective rim diameters. (3) The + shows where a letter indi rating" of a tyre may appear in the e.g., 155 + R13 incorporates 155SR 155VR13. Most common rating lett	10	Free		207712E	1/81	6/84	
		<ul> <li>but can include F, M, N, P, Q, R, T, and U ( the effect of the symbol + is to disregard speed ratings).</li> <li>(4) The letter "C" can also appear after the rim diameter and should be disregarded, e.g., 185R14C 500-16C</li> <li>(5) Group markings occur and vary according to country of origin. If a size incorporated in a group marking appears in the list of sizes in TDL 385, the tyre or tube with group marking is deemed to be included in TDL 385, e.g., 575/600/640-15 includes the sizes 575-15, 600-15, and 640-15</li> <li>(6) Any mud and snow tyres in the sizes listed may be entered at the concessionary rate of duty EXCEPT where indicated by the symbol [*]</li> </ul>							
		Cars, vans, and light commercial ve Tyres	ehicles						
		10 in. rim diameter (or 255 mm) 5.20 + 10 165/70 + R10	145 + R10						
		12 in. rim diameter (or 305 mm) 4.40 + 12 4.40/125 5.20 + 12 5.35 + 12 5.50 + 12 5.60 + 12	Y78 + 12 Z78 + 12 125/5.35 + 12 155/6.15 + 12 140 + R12 145 + R12						
		150 + R126.00 + 126.15 + 126.2 + 126.20 + 12	155 + R12 175/70 + R12 P155/80 + R12						
		13 in. rim diameter (or 330 mm)	YR78 + 12 ZR70 + 12						
		5.20 + 13 5.50 + 13 5.60 + 13	205/60 + 13 215/60 + R13 P205/60 + R13 P215/60 + R13						
		5.90 + 13 175/70 + R13 6.00 + 13 6.2 + 13 [*]6.40 + 13 [*]6.50 + 13 6.70 + 13	[*]185/70 + R13 195/70 + R13 P175/70 + R13 [*]P185/70 + R13 P195/70 + R13						
		6.9 + 13 7.00 + 13 7.50 + 13 155/6.15 + 13	P155/80 + R13 [*]P165/80 + R13 P175/80 + R13 P185/80 + R13						
		A78 + 13 [*]B78 + 13 [*]C78 + 13 C70 + 13 145 + R13	BR60 + 13 CR60 + 13 ZR70 + 13 AR70 + 13 [*]BR70 + 13 CR70 + 13						
		150 + R13 155 + R13 160 + R13 [*]165 + R13 170 + R13 175 + R13 185 + R13 185 + R13 145 - R13	YR78 + 13 ZR78 + 13 [*]AR78 + 13 BR78 + 13 CR78 + 13 DR78 + 13						
		14 in. rim diameter (or 355 mm) 5.00 + 14 5.20 + 14	155 + R14 165 + R14						