

TARIFF DECISION LIST No. 619—continued
DETERMINATIONS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Concession Code	Effective	
			Normal	Pref.			From	To*
HO	82.02.021 Deter'n	Gang saw blades for wood sawing	30	Aul Free Can 20 DC 20 Pac Free	..	207797D	1/86	..
HO	82.04.011 Deter'n	Screwdrivers, non-ratchet, having straight fixed blades or detachable bits measuring from 31.75 mm to 381 mm (1 1/4 in. to 15 in.) both inclusive, with shanks measuring from 3.63 mm to 11.11 mm (1/7 in. to 7/16 in.) both inclusive, and sets comprising any of the foregoing; EXCLUDING: (1) Screwdrivers of beryllium copper (2) Blades and blanks, when declared by a manufacturer for use by him only in making screwdrivers (3) Hexagonal head screwdrivers for Allen screws (4) Valve core screwdrivers (NOTE: The blade/bit length is to be measured between the point where the shank meets the handle and the tip of the working edge. Thickness is to be taken in the case of circular shanks as the diameter, and in the case of square and hexagonal shanks the length of a cross-sectional side).	17.5	Aul 2 Can 10 Pac Free	..	207806G	1/83	12/83
HO	82.04.011 Deter'n	Screwdrivers, non-ratchet, having straight fixed blades or detachable bits measuring from 31.75 mm to 381 mm (1 1/4 in. to 15 in.) both inclusive, with shanks measuring from 3.63 mm to 11.11 mm (1/7 in. to 7/16 in.) both inclusive, and sets comprising any of the foregoing; EXCLUDING: (1) Screwdrivers of beryllium copper (2) Blades and blanks, when declared by a manufacturer for use by him only in making screwdrivers (3) Hexagonal head screwdrivers for Allen screws (4) Valve core screwdrivers (NOTE: The blade/bit length is to be measured between the point where the shank meets the handle and the tip of the working edge. Thickness is to be taken in the case of circular shanks as the diameter, and in the case of square and hexagonal shanks the length of a cross-sectional side).	17.5	Aul Free Can 10 Pac Free	..	207807E	1/84	..
HO	84.23.011 Deter'n	Front end loaders, whether or not assembled, as defined by SAE Standard SAE J1057a (published in the Society of Automotive Engineers, Inc Handbook) which cannot rotate through the horizontal plane without movement of the wheels with a static tipping load in full turn capacity up to and including 16,000 kg as measured to SAE Standard J732c This measurement shall be applied to these loaders equipped to the normal standard specifications as offered for sale excluding tyre ballast	35	Aul 20 Can 25 Pac Free	..	207808C	1/83	12/83
HO	84.23.011 Deter'n	Front end loaders, whether or not assembled, as defined by SAE Standard SAE J1057a (published in the Society of Automotive Engineers, Inc Handbook) which cannot rotate through the horizontal plane without movement of the wheels with a static tipping load in full turn capacity up to and including 16,000 kg as measured to SAE Standard J732c This measurement shall be applied to these loaders equipped to the normal standard specifications as offered for sale excluding tyre ballast	35	Aul 15 Can 25 Pac Free	..	207809A	1/84	12/84
HO	84.23.011 Deter'n	Front end loaders, whether or not assembled, as defined by SAE Standard SAE J1057a (published in the Society of Automotive Engineers, Inc Handbook) which cannot rotate through the horizontal plane without movement of the wheels with a static tipping load in full turn capacity up to and including 16,000 kg as measured to SAE Standard J732c This measurement shall be applied to these loaders equipped to the normal standard specifications as offered for sale excluding tyre ballast	35	Aul 10 Can 25 Pac Free	..	207810E	1/85	12/85
HO	84.23.011 Deter'n	Front end loaders, whether or not assembled, as defined by SAE Standard SAE J1057a (published in the Society of Automotive Engineers, Inc Handbook) which cannot rotate through the horizontal plane without movement of the wheels with a static tipping load in full turn capacity up to and including 16,000 kg as measured to SAE Standard J732c This measurement shall be applied to these loaders equipped to the normal standard specifications as offered for sale excluding tyre ballast	35	Aul 5 Can 25 Pac Free	..	207811C	1/86	12/86
HO	84.23.011 Deter'n	Front end loaders, whether or not assembled, as defined by SAE Standard SAE J1057a (published in the Society of Automotive Engineers, Inc Handbook) which cannot rotate through the horizontal plane without movement of the wheels with a static tipping load in full turn capacity up to and including 16,000 kg as measured to SAE Standard J732c This measurement shall be applied to these loaders equipped to the normal standard specifications as offered for sale excluding tyre ballast	35	Aul Free Can 25 Pac Free	..	207812A	1/87	..
HO	84.25.011 Deter'n	Haymaking tedders, whether or not assembled, including multifunctional type machines	20	Aul 15 DC 15 Pac Free	..	207813K	1/83	12/8