

Post Office Schedule of Building Contract of \$20,000 or More in Value

Name of Work	Successful Tenderer	Amount of Tender Accepted \$
Taneatua new Telephone Exchange POHQ 3/403/2	Hawkins Construction Ltd. F. K. McINERNEY, Director-General.	59,900

LPG Fuel System Approvals—Concessional Fuel Cylinder Approvals

PURSUANT to regulation 90B of the Traffic Regulations 1976* (as inserted by the Traffic Regulations 1976 Amendment No. 7) and pursuant to the powers delegated to me by the Secretary for Transport, I, Trevor Alan Lister, Senior Automotive Engineer, hereby approve the LPG fuel cylinders listed in Schedule I hereunder for inclusion in any LPG fuel system installed and operated in accordance with the requirements of New Zealand Standard NZS 5422, Part 1, 1980 (and any standard made in amendment thereto or in substitution therefor) subject to the conditions set out in Schedule II hereunder.

SCHEDULE I

LPG FUEL CYLINDERS MANUFACTURED PRIOR TO 1 MARCH 1980

MOT Reference	Manufacturer	Drawing Number	Material	Specification	Inspection Authority	Nominal Water Capacity (litres)	Working Pressure Rating (MPa)	Test Pressure (MPa)
AF LO3C 013	Brunner Eng. U.S.A.	S 2140 (18×36)	Steel	ASME 8/1	ASME	135.1 (35.7 U.S. gal)	1.94 (281 psi)	2.91
AF LO3 014		S 2141 (20×42)	Steel	ASME 8/1	ASME	194.6 (51.4 U.S. gal)	1.94 (281 psi)	2.91

SCHEDULE II

CONDITIONS OF APPROVAL

LPG fuel cylinders are approved subject to the following conditions—

1. That they be permanently and clearly marked, on a suitably attached metal plate, with characters not less than 6 mm high if space permits but in any case not less than 3 mm high, displaying the following information:

- The specification to which the cylinder was manufactured.
- The manufacturer's name or mark, and the serial number of the cylinder.
- The date of the original cylinder inspection and the identification mark of the inspection authority who made the inspection.
- The date of any periodic cylinder test and the identification mark of the cylinder testing station who made each test.
- The cylinder test pressure.
- The nominal water capacity of the cylinder.
- The tare weight of the cylinder.

2. That they be clearly marked or labelled to indicate that the cylinder is suitable for use with LPG.

3. That they be provided with valve threads and fittings which provide the following functions:

- Filling connection incorporating a non return valve.
- Service valve incorporating an excess flow valve.
- Contents gauge.
- Safety valve.

(e) A fixed liquid level indicator or an automatic fill shut off device which prevents the cylinder being filled beyond 85 percent of the total cylinder capacity.

Valves and fittings shall have a service pressure rating of at least that of the cylinder to which they are fitted and shall be dimensioned, threaded and marked in accordance with the requirements of section 2.3 of New Zealand Standard NZS 5422 "The use of LPG and CNG Fuels in Internal Combustion Engines—Part 1 LPG Fuel".

4. That they be tested at periods not exceeding five years in accordance with the requirements of Australian Standard AS 2337-1980 and in accordance with the periodic test requirements laid down in the specification to which the cylinder was manufactured.

5. That they be fitted to a motor vehicle in such a position that they will not be subjected to the direct rays of the sun, either by fitting them within a suitable vehicle compartment, or by providing a suitable shield if the cylinders are fitted to the exterior of the vehicle.

NOTES: The effect of this notice is to allow the continued use of LPG fuel cylinders which are known to have been imported into New Zealand prior to the introduction of the Dangerous Goods (Class 2—Gases) Regulations 1980 and which were acceptable under the previous dangerous goods requirements, but whose working pressure rating would disqualify them for approval for general use under the Traffic Regulations 1976. They are approved subject to the additional proviso that they must not be exposed to direct sunlight (to reduce the possibility that solar radiation would raise the temperature of the contents of the cylinder such that the developed pressure of the cylinder contents exceeded the working pressure rating of the cylinder).

The terms of this approval do not allow the continued importation of such LPG fuel cylinders.

Dated at Wellington this 3rd day of May 1983.

T. A. LISTER, Senior Automotive Engineer.

*S.R. 1976/227

- Amendment No. 1: S.R. 1978/72
- Amendment No. 2: S.R. 1978/301
- Amendment No. 3: S.R. 1979/128
- Amendment No. 4: S.R. 1980/31
- Amendment No. 5: S.R. 1980/115
- Amendment No. 6: S.R. 1981/158
- Amendment No. 7: S.R. 1981/311
- Amendment No. 8: S.R. 1982/93