THE NEW ZEALAND GAZETTE

Tariff Notice No. 1983/107—Applications for Approval

NOTICE is hereby given that applications have been made to the Minister of Customs for concessionary entry of the following goods at the rates of Customs Duty shown:

| Port | Appn. No. | Tariff Item | Goods | Rates of Duty | | Par II |
|----------|---------------|------------------------|--|----------------|----------------|-----------|
| | INU. | | | Normal | Pref. | Re |
| WN | 2836 | 19.03.000 | Air dried instant pasta, for use as a raw material in making instant pasta | Free* | Free* | |
| WN WN | 2876 2820 | 30.02.009 32.09.059 | Parvo-vaccine, for use on pigs Fluoricon 271-7 (silicones AI: tri-chloro-fluoro-methane solv), as a | Free* Free* | Free Free | |
| VN .K | 2834 22009 | 32.13.009 34.05.001 | release agent for polyurethane castable elastomer mouldings Ink for printing labels, for rubber backed mats Reopol 88 glass polishing compound, for polishing edges of sheet glass | Free* Free* | Free* Free* | |
| H | 1036 | 37.08.009 | after grinding Ilford nuclear research emulsion, for medical and institutional research | Free* | Free* | |
| /N | 2818 | 38.11.029 | in conjunction with electron microscopes Baythroid, for use as an insecticide, quantities of 5 000 kg p.a. | Free* | Free* | |
| 'N | 2324 | 38.11.031 | Bayleton BM, for use on wheat and barley | Free* | Free* | |
| 'N | 2822 | 38.11.059 | Amatin 74WP, containing 74 percent Divron and 4 percent W/W Methabenthiazuron, for the control of weeds | Free* | Free* | |
| K | 21986 | 38.19.001 | F.P.R. 12 cement, for cementing in basic or zirconia inserts when repairing ladle gate valve sets | Free* | Free* | |
| 'N | 2819 | 39.01.211 | Dispercoll TP KA 8299 polyester polyurethane, for use in making adhesives based on highly plasticized PVC, 5000 kg p.a. | Free* | • • | |
| 'N K | 2806 21875 | 39.02.211 39.02.378 | Rocagil 1295, a chemical grout for rock and concrete water tightening High density polyethylene film, silicone coated one side, for making | Free* | Free* | |
| N | 717 | 39.07.599 | pressure sensitive tape Cogged endless acetal belts, for use on cheese wrapping machines, for | Free* | Free* | |
| 'N | 2847 | 39.07.599 | formation of individually wrapped cheese slices Computer data tabs for index tabbing, for line flow computer paper as | Free* | Free* | |
| H | 1033 | 39.07.599 | accessories to filing computer stationery Trimline vinyl tips 080-4, 062-8, 437-6, and 112.5, for use in making | Free* | Free* | |
| K | 21902 | 39.07.599 | radio telephone equipment | | | |
| 'N | 2830 | 40.09.001 | T tape, perforated layflat irrigation hose Trellheat furnace door cooling hose | Free* Free* | Free* | |
| 'N | 2714 | 40.14.049 | Rubber cups for use on seed drills | Free* | Free* | |
| H N | 1032 715 | 48.07.151 73.11.013 | Siliconised release paper, used as backing for self-adhesive paper Angle steel section, 120 mm × 120 mm × 13 mm thick, 200 mm × 200 mm × 28 mm thick, 140 mm × 140 mm × 15 mm thick, all to standard 52-3 DIN 17100 quality, to fabricate tower sections for Kroll | Free* 5* | Aul Free | |
| N | 716 | 73.11.031 | cranes at the Clyde dam site Rectangular hollow section steel, 12 mm × 100 mm ×100 mm × 6.3 mm, to standard BS 4360 grade 50C and charpy V notch impact tests, at -15°C required, or to standard EV25 72FE 430C, or to standard RST 42-3, to fabricate tower sections for Kroll cranes at the Clyde dam | 5* | Aul Free | |
| K | 21811 | 73.40.069 | site Collared drop forged lifting eye bolts and eye bolt blanks to B.S. 529, | Free* | Free* | |
| K | 21979 | 73.40.069 | part l Tactoo insulation hangers, being a flat galvanised base with nail like | Free* | Free* | |
| H | 1034 | 74.03.019 | spike and lock washer Brass strip 7.14 mm × 1.2 mm, 7 mm × 1.6 mm, and 14 mm × | Free* | Free* | |
| Н | 1028 | 76.03.001 | 2.64 mm, for making electrical components Wrought plates and sheets of aluminium, worked, Topas Dessin, half head temper, pliable, minimum bending radius of 6 mm in cold bend- | Free* | Free* | |
| K | 22008 | 84.08.011 | ing operations, for structural panels for buildings Air operated pneumatic cylinders, stainless steel, for operating LK | Free* | Free* | |
| K | 21984 | 84.10.029 | stainless steel butterfly valves Hydraulic pump tool, to be used in conjunction with push pull jacks, for repairing bulldozers, four way valve type push pull, discharge flow | Free* | Free* | |
| K | 21852 | 84.10.029 | 4.6 cc/700 kg/cm ² , discharge pressure 129 cc/25 kg/cm ² Metripumps types G, Q and L, positive stroke return pumps, flow rates | Free* | Free* | |
| K | 21864 | 84.10.029 | up to 7800 litres/hr., pumpheads in stainless steel or PTFE Micro pumps, peristaltic pumps for laboratory and critical limit applications, e.g. liquors, suspensions, slurries, capacity up to 12.5 litres/hr., | Free* | Free* | |
| K | 21865 | 84.10.029 | at pressures up to 2 kg/cm ² Minerva centrifugal single stage pumps, self-priming or portable, with delivery connnections of a nominal internal diameter exceeding 77 mm, for industrial and marine applications, capacity ranges at 50 Hz 20 m ³ /hr., to 300 m ³ /hr., 1500 US. G.P.M., at 60 Hz 22 m ² /hr., to | Free* | Free* | |
| K | 21853 | 84.10.029 | 400 m ³ /hr., 2000 US. G.P.M. Mono E range metripumps, variable stroke spring return metering pumps of modular construction, pumphead flow rates from a few milli- litres per hour to 27 litres/hr., maximum working pressures up to 138 | Free* | Free* | |
| K | 21854 | 84.10.029 | bar (2000 lb/in.²) pumpheads of stainless steel or plastic Mono S range metripumps, compact diaphragm metering pump, constructed in alluminium alloy pump casing, pumphead is polypropylene with PTFE diaphragm, performance S35 3.5 litres/hr., at discharge pressure up to 3.5 bar (50 lb/in.²), and S120 12 litres/hr., output at | Free* | Free* | |
| K | 21861 | 84.10.029 | discharge pressure up to 3.5 bar MPL centurion C100 metering pumps, i.e., positive displacement metering pumps, capacity up to 198 litres/hr. per head pressures up to | Free* | Free* | |
| K | 21858 | 84.10.029 | 63 kg/cm ² MPL series type K-twin metering pumps, i.e., two independently adjustable pumpheads driven from a single electric motor, capacity up to 273 litres/hr., per head at pressures up to 49 kg/m ² , in stainless steel or polypropylene | Free* | Free* | |