## THE NEW ZEALAND GAZETTE

No. 145

## TARIFF DECISION LIST No. 711-continued

DETERMINATIONS—continued

-	Tariff Item No.	Goods	Rates of Duty		Part		Effective	
Port			Normal	Pref.	II Ref.	cession Code	From	To*
но	90.28.001 Deter'n	Gas detection systems, peculiar for use in commercial and/or industrial environments, which measure and report concentrations of flamable or toxic gases in the air via alarm and/or analogue		Aul Free Can 15 Pac Free	•••	209725H	1/85	
НО	90.28.001 Deter'n	Moving iron ammeters and voltmeters, flush mounting, quadrant scale, to accuracy class 1.5 and having face sizes from 72 mm to 144 mm square	35	Aul 15 Can 15 Pac Free	••	209720G	1/84	12/84
		Moving coil and moving coil/rectifier ammeters and voltmeters, flush mounting, having face areas of between 5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales NOTE: circular, sector and quadrant type scales are illustrated in Fig. 2 on pages 11 and 12 of B.S. 3693, PART 1, 1964, "The Design of Scales and Indexes"						
но	90.28.001 Deter'n	Design of Scales and Indexes" Moving iron ammeters and voltmeters, flush mounting, quadrant scale, to accuracy class 1.5 and having face sizes from 72 mm to 144 mm square	35	Aul 10 Can 15 Pac Free		209721E	1/85	12/85
		Moving coil and moving coil/rectifier ammeters and voltmeters, flush mounting, having face areas of between 5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales						
	00.28.001	NOTE: circular, sector and quadrant type scales are illustrated in Fig. 2 on pages 11 and 12 of B.S. 3693, PART 1, 1964, "The Design of Scales and Indexes"	25	A 1 - 5		2007220	1/97	12/06
но	90.28.001 Deter'n	Moving iron ammeters and voltmeters, flush mounting, quadrant scale, to accuracy class 1.5 and having face sizes from 72 mm to 144 mm square Moving coil and moving coil/rectifier ammeters and voltmeters,	35	Aul 5 Can 15 Pac Free	••	209722C	1/80	12/86
•		flush mounting, having face areas of between 5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales						
но	90.28.001	NOTE: circular, sector and quadrant type scales are illustrated in Fig. 2 on pages 11 and 12 of B.S. 3693, PART 1, 1964, "The Design of Scales and Indexes" Moving iron ammeters and voltmeters, flush mounting, quadrant	35	Aul Free		209723A	1/87	
	Deter'n	scale, to accuracy class 1.5 and having face sizes from 72 mm to 144 mm square Moving coil and moving coil/rectifier ammeters and voltmeters, flush mounting, having face areas of between 5184 square		Can 15 Pac Free				
		millimeters and 9216 square millimeters and having sector, quadrant or circular scales NOTE: circular, sector and quadrant type scales are illustrated in Fig. 2 on pages 11 and 12 of B.S. 3693, PART 1, 1964, "The Design of Scales and Indexes"						
НО	90.28.001 Deter'n	Portable electrically powered gas leak detector, gas detector and gas monitor and smoke warning alarms	35	Aul 15 Can 15 Pac Free	••	209726F		12/84
но	90.28.001 Deter'n	Portable electrically powered gas leak detector, gas detector and gas monitor and smoke warning alarms	35	Aul 10 Can 15 Pac Free		209727D		12/85
но	90.28.001 Deter'n 90.28.001	Portable electrically powered gas leak detector, gas detector and gas monitor and smoke warning alarms Portable electrically powered gas leak detector, gas detector and	35 35	Aul 5 Can 15 Pac Free Aul Free		209728B 209729L	1/80	12/86
но	Deter'n 90.28.001	gas monitor and smoke warning alarms Post payment self-service petrol dispensing systems	35	Can 15 Pac Free Aul 15		209730D	·	12/84
но	Deter'n 90.28.001 Deter'n	Post payment self-service petrol dispensing systems	35	Can 15 Pac Free Aul 10 Can 15		209731B	1/85	12/85
но		Post payment self-service petrol dispensing systems	35	Pac Free Aul 5 Can 15	•••	209732L	1/86	12/86
но		Post payment self-service petrol dispensing systems	35	Pac Free Aul Free Can 15 Pac Free	••	209733J	1/87	
но	90.28.001 Deter'n	Power factor correction systems, including power factor controllers and ancillary equipment mounted in a common cubicle and designed to measure and automatically control the overall power factor in a 3-phase electrical installation, and such power factor controllers when imported separately	35	Aul 15 Can 15 Pac Free	•	209734G	1/84	12/84
НО	90.28.001 Deter'n		35	Aul 10 Can 15 Pac Free	••	209735E	1/85	12/85
НО	90.28.001 Deter'n		35	Aul 5 Can 15 Pac Free	••	209736C	1/86	12/86