

Tariff Notice No. 1984/180—Application for Variation of Determination

NOTICE is hereby given that an application has been made for variation of a current determination of the Minister of Customs as follows:

Port	Appn. No.	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Concession Code	Effective	
				Normal	Pref.			From	To*
		84.47.001 Deter'n	<p>CURRENT DETERMINATION:</p> <p>Woodworking machinery; Automatic firewood saws Bandsaws with throat capacity not exceeding 535 mm (21 in) Box nailing machines Breast benches Circular breakdown saws Circular saw benches, hand-feed, including builders treadle saw benches, with blade diameter not exceeding 360 mm Cut-off saws, pendulum type with motor not exceeding 3.75 kW (5 h.p.) and with blade diameter not exceeding 500 mm (20 in) Docking saws Dovetailing machines with single spindle and manual feed Drill presses, wall mounting, radial type not exceeding 22.2 mm capacity in mild steel Horizontal dowel boring machines, not exceeding 25 mm capacity in mild steel Log cut-off swing saws Post peelers Post pointers Precision veneer trimming saws Radial arm saws, overhead crosscut saws, trenching machines and mitreing machines, with a blade diameter not exceeding 360 mm Splitting saws Tenoning machines, single spindle Veneer presses manually operated, single daylight, for cold pressing; Vertical breakdown saws Wood debarking machines, Rosser head not exceeding 1425 mm (56 in) diameter and ring type not exceeding 1020 mm (40 in) diameter</p>	40	Aul 15 Can 25 DC 25 Pac Free		207967E	1/84	12/84
H.O.	28538	84.47.001 Deter'n	<p>REQUESTED DETERMINATION:</p> <p>Woodworking machinery; Automatic firewood saws Bandsaws with throat capacity not exceeding 535 mm (21 in) Box nailing machines Breast benches Circular breakdown saws Circular saw benches, handfeed, including builders' treadle saw benches, with blade diameter not exceeding 360 mm Cut-off saws, pendulum type with motor not exceeding 3.75 kW (5 h.p.) and with blade diameter not exceeding 500 mm (20 in) Docking saws Dovetailing machines with single spindle and manual feed Drill presses, wall mounting, radial type not exceeding 22.2 mm capacity in mild steel Horizontal dowel boring machines, not exceeding 25 mm capacity in mild steel Log cut-off swing saws Post peelers Post pointers Precision veneer trimming saws Radial arm saws, overhead crosscut saws, trenching machines and mitreing machines, with a blade diameter not exceeding 305 mm Splitting saws Tenoning machines, single spindle Veneer presses manually operated, single daylight, for cold pressing; Vertical breakdown saws Wood debarking machines, Rosser head not exceeding 1425 mm (56 in) diameter and ring type not exceeding 1020 mm (40 in) diameter</p>						