## THE NEW ZEALAND GAZETTE

## TARIFF DECISION LIST No. 723—continued

APPROVALS—continued

Port	Tariff	Goods	Rates o	Rates of Duty		Con-	Effective	
	Item No.		Normal	Pref.	II Ref.		From	To*
DN	59.03.001	Bonded fibre, being non-woven fabric composed of polyester	Free			901751J	12/81	9/92
		continuous filament fibres, when declared; (1) by a manufacturer for use by him, only in making						
		footwear; or (2) by an importer for sale to a manufacturer for use by him				• .		
НО	59.08.002	only in making footwear Coated muslin, being woven polyethylene and/or rayon fabrics coated with liquid polyethylene, for use in making adhesive tapes	Free			209816E	6/84	6/88
DN	59.12.029		Free	Free	15	917729K	11/81	9/92
	60.01	(2) by an importer that it will be sold by him, only to a manufacturer for making footwear	<b></b>		1.5	2000201	0.40.4	0.400
но	60.01	Fabrics narrowed at intervals, knitted or lockstitched, in the piece or cut singly, but not including fabrics pressed or end finished, on condition that they will be used in the	Free	Free	15	209828J	9/84	9/90
DN	64.05.000	manufacture of neckties Arc supports, when declared by an importer for supply only to	Free	Free	99	108859K	7/78	9/92
НО	69.01	hospitals, chiropodists and doctors All goods of heading 69.01 but excluding the following: Goods having a maximum service rating below 1100°C (2100°F)	Free	Free	15	209823H	10/84	9/85
		NOTE: Any applications for products covered by the above exclusion must be supported by the following information;						
		(a) maximum service temperature (b) chemical composition						
		(c) modules of rupture (d) cold crushing strength						
		(e) apparent porosity (f) density						
шо	69.02	(g) thermal conductivity (h) full details of end use	Fees	Face	1.5	2000245	10/04	0.40.5
НО	69.02	All goods of heading 69.02 but excluding the following: All refactory products having an alumina (A1 <sub>2</sub> 0 <sub>3</sub> ) content between 25% and 90% by weight	Free	Free	13	209824F	10/84	9/85
		NOTE: Any applications for products covered by the above exclusion must be supported by the following information;						
		(a) maximum service temperature (b) chemical composition						
		(c) modules of rupture (d) cold crushing strength						
		(e) apparent porosity (f) density						
DN	69.09.002)	(g) thermal conductivity (h) full details of end use Filter cores, peculiar to use in refrigeration installations	Free	Free	99	1000004	7,170	0.00
DIN	69.09.003) 69.09.019)	Therefores, pecunal to use in renigeration instanations	Tice	Tiec	77	108990A	7/78	9/92
DN .	69.14.001) 69.14.009)	Counterfaces of porcelain and of porcelain and rubber	Free	Free	99	109002L	3/79	9/92
DN	Section XV	Fittings, mountings and trimmings commonly used for making or repairing motor vehicles, as may be approved;	Free	Free	15	912905H	6/84	9/92
		APPROVED: Bonnet handles, plain or ornamental, which when lifted or turned, lock or unlock the bonnet						
		Brackets for parcel racks Escutcheon plates						
		Floorboard fasteners Hand grips of metal, covered with vulcanite or similar material,						
		commonly used on passenger service vehicles Handles, door, being parts of locksets						
		Handles, door Handles, glass fitting						
		Handles, seat Handles, metal, bored or unbored						
		Hooks, rope Mouldings, metal, being so shaped as to identify them as parts of motor vehicles, plated, polished or enamelled, but not						
		drilled or otherwise worked Recess plates						
		Slide door fittings Van door holders, dovetails, door retaining catches, coat hooks, finished ends, trim fasteners, moulding fasteners, footman loops				* }		
		and striker plates Ventilators and air extractors for buses						
		Window regulators or lifters EXCLUDING: fittings for outward-opening caravan windows						
DN DN	73.11.001 73.20.059	Sheet piling Tongued and grooved flanges of steel, when declared by a	Free Free	Free Free		109183C 109465D	7/78 7/78	9/92 9/92
		manufacturer for use by him only in making refrigeration stop valves	1100	1100	77	1077031	1/10	7/72
DN	73.40.069	Bushes, insert, threaded externally and internally, or made from spirally wound wire to provide fastenings in soft metal	Free	Free	15	109583J	7/79	9/92
		and plastics						