

Tariff Notice No. 1984/216—Applications for Approval—continued

Port	Appn. No.	Tariff Item	Goods	Rates of Duty		Part II Ref.
				Normal	Pref.	
AK	29554	73.40.069	Carnation clips to be used to support the calyx of the carnation flower	Free*	Free*	99
WN	694	73.40.069	Sleeves or wedges for anchoring pre-stressed wire and strand for use in prestressed concrete structures and sections	Free*	Free*	99
WN	607	74.03.031	Soundronic or seam welding wire of unalloyed copper	Free		..
WN	668	74.10.000	Xersin wick solder remover type X-AA yellow 1.5 mm × 1.5M rolls	Free*	Free*	99
WN	667	74.10.000	Xersin wick solder remover type X-BB blue, 2.77 mm × 1.5M rolls	Free*	Free*	99
AK	29583	74.19.009	Brass aerators for inclusion in taps manufactured in New Zealand	Free*	Free*	15
WN	637	83.01.011	Chubb double cylinder rim locks (AVA patented 10-disc detainer mechanism) models 4L 66 and 67	Free		..
AK	29627	83.01.011	Lowe and Fletcher locks model A/T3 for use in the making of sliding door handles and architectural joinery	Free		..
CH	253	83.02.009	Blair Twistlock PD151 Mark 3	Free*	Free*	15
AK	29592	83.15.009	Desolder braid, a flux impregnated copper braid which when moderately heated takes up the solder from joints and adheres to the Braid	Free*	Free*	15
CH	246	84.10.029	Jung WC-fix model U3K pump with a flow rate and pressure of 40 litres per minute; maximum head 3 metres; 1 1/4" BSP horizontal discharge branch; "Noryl" plastic pump body and top cover, "Hostaform" GFR impeller, stainless steel encapsulated motor and stainless steel rotor shaft; suitable for continuous operation at a maximum water temperature of 40°C (104°F) with partly immersed motor, 60°C max (140°F) if fully immersed; used for pumping domestic sewage	Free*	Free*	10
AK	29568	84.10.029	Mini syrup pumps for use in the making of beverage dispensing systems	Free*	Free*	10
AK	29576	84.10.029	Orian air operated fluid transfer pumps	Free*	Free*	10
WN	513	84.10.029	Stork model HCR31, 5A-8/5 centrifugal process pumps to American petroleum institute standard 610 used as flare drum heating medium pumps, 80 mm suction, 50 mm discharge and made of cast steel, capacity of 3.314m ³ per second maximum discharge head 52.7 meters and operating temperatures from 0°C at start up to 200°C, for pumping thermia 32 heat transfer oil with a viscosity from 300 CST to 10CST	Free*	Free*	15
AK	29630	84.11.011	Nash CL-702 pump to increase the capacity of ecinco vacuum filter	Free*	Free*	10
AK	29503	84.11.061	Dri-clave evacuation fans for use in high volume dental evacuation system	Free		..
WN	739	84.11.061	Parts for fabrication of Engart B20 and B40 bifurcated fans used as ventilation of underground coalmines	Free		..
AK	29528	84.18.031	Flakt electrostatic precipitators type FAC 37.5F to remove contaminants from pulpmill exhaust gases and retrieve process chemical for re-use	Free*	Free	10
AK	29558	84.19.039	Auger filler machine for filling 50 to 100gm packets with mustard powder	Free*	Free*	10
WN	663	84.19.039	Arpac bagging machine for clothing	Free*	Free*	10