

Tariff Notice No. 1984/227—Applications for Approval—continued

Port	Appn. No.	Tariff Item	Goods	Rates of Duty		Part II Ref.
				Normal	Pref.	
DN	864	73.25.009	28 mm ungalvanised steel wire rope super grade ultra high tensile minimum breaking load 60 tonnes, for incorporation into electric overhead travelling cranes Clyde Dam	Free*	Free	15
WN	824	73.27.029	Bekaert "casanet plastic" cross welded steel mesh, galvanised after welding and then blue plastic coated in 100ft rolls, shrink packed	Free*	Free*	15
AK	29871	73.32.029	ISO metric series 12.9 grade hexagonal socket head cap screws, imperial hexagonal socket head cap screws with BSW threads manufactured to BS 2470	Free*	Free*	15
WN	776	73.40.069	Stainless steel snap rings 121 mm OD × 30 mm wide × 0.38 mm thick for use in making filter bags	Free*	Free*	15
AK	29767	76.10.011	Collapsible aluminium tubes internally lacquered with an I.D. less than 25 mm for packing of pharmaceuticals	Free*	Free*	15
AK	29937	76.16.059	Di cast aluminium boxes models H2201 and H2206 for house electrical, electronic equipment for manufacturers and hobbyists	Free*	Free*	15
WN	765	83.01.011	ERA cylinder window and door locks No. 802, 804 and 806	Free		
H.O.	65620	84.08.011	Air actuators for Whitey and Nupro valves	Free*	Free*	10
WN	804	84.08.011	Pneumatic cylinder actuators and mounting kits for supply to Natural Gas Corp	Free*	Free*	10
AK	29873	84.10.029	F1 series of Volvo hydraulic pump/motors	Free*	Free*	10
WN	695	84.10.029	Plasilac flow sanitary stainless steel centrifugal pumps; ZMD single stage centrifugal pump, inlet and outlet outside diameter 63.5 mm, flow rate of 2,000 to 45,000 L/H, pressure up to approximately 12 Kp/CM ² for use in dairy, brewery, food and chemical industries	Free*	Free*	10
			ZMH-1 two stage centrifugal pump, inlet 51 mm and outlet 38 mm (outside diameters), flow rate of 500 to 30,000 L/H pressure 11 kP/CM ² for use in dairy, brewery, food and chemical industries			
			ZMH-2 two stage centrifugal pump, inlet 76 mm and outlet 63.5 mm (outside diameters), flow rate of 15,000 to 50,000 L/H, pressure 11 kP/CM ² for use in dairy, brewery, food and chemical industries			
			ZMH-4 two stage centrifugal pump, inlet 101.6 mm and outlet 63.5 mm (outside diameters), flow rate of 20,000 to 130,000 L/H, pressure 7 Kp/CM ² for use in dairy, brewery, food and chemical industries			
AK	29834	84.17.009	Cyrel solvent recovery units for the reclaiming of solvent washout chemistry used in the production of flexographic printing plates	Free*	Free*	10
AK	29920	84.17.009	Saw-tooth hardening machine for the heat treatment hardening of saw teeth after sharpening	Free*	Free*	10
AK	29874	84.17.009	Spiraflo must cooler 15 element T4 5/3-6	Free*	Free*	10
WN	791	84.17.009	Vapour pressure bath for laboratory petroleum testing	Free*	Free*	10
AK	29876	84.18.039	Earth Filter-O-mat 65 for filtering blackcurrent juice	Free*	Free*	10