

TARIFF DECISION LIST No. 679—continued

APPROVALS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Con-cession Code	Effective	
			Normal	Pref.			From	To*
CH	84.59.059	Rapid granulators, models GK205K and GK3026K	Free	Free	10	909986H	12/83	9/90
AK	84.59.059	Remote head compression tools, Electropar brand, types 12, 60, and 100	Free	Free	10	926748E	9/83	9/91
AK	84.61.021	Cocks and valves; EXCLUDING: (1) Penstocks, floodgates (2) Valves, gate, of the following types; (a) Stainless steel 76 mm to 458 mm (3 in. to 18 in.) or cast iron 76 mm to 356 mm (3 in. to 14 in.) specifically designed for use with pulp or paper stock (b) Brass 6 mm (¼ in.), 9 mm (⅜ in.), 12 mm (½ in.), 19 mm (¾ in.), and 25 mm (1 in.) (c) 6 mm to 102 mm (¼ in. to 4 in.) of any kind of bronze or brass (d) Flanged, cast iron, to B.S. 3464, other than outside screw and yoke types, (nominal metric equivalent) sizes 50 mm (2 in.), 65 mm (2½ in.), 75 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.), 200 mm (8 in.) (e) Flanged, cast iron, to B.S. 3464, with indicators, sizes 76 mm (3 in.), 100 mm (4 in.), and 150 mm (6 in.) 200 mm (8 in.) (3) Valves, globe, of any kind of bronze, peculiar for use with steam at working pressures of 345 kPa (50 p.s.i.) or over of the following types; (a) Stainless steel seats, screwed 9.5 mm to 51 mm (⅜ in. to 2 in.) (b) Yoke top with bronze or stainless steel seats, flanged (c) Angle, yoke top with bronze or stainless steel seats, flanged, 20 mm to 150 mm (¾ in. to 6 in.) (d) Valves, safety or relief, springloaded, screwed or flanged, with bronze or stainless steel seats, 10 mm to 100 mm and brass seats, 12 mm (e) Fibre or teflon seats, screwed, sizes 12 mm to 51 mm (½ in. to 2 in.) (f) Flanged bonnet top 19 mm to 77 mm (¾ in. to 3 in.) with bronze or stainless steel seats and a working pressure of up to 865 kPa (125 p.s.i.) (g) Flanged regulating check angle or straight type 19 mm to 153 mm (¾ in.) to 6 in. with bronze or stainless steel seats and a working pressure up to 1725 kPa (250 p.s.i.) (h) Foot operated, quick action or slow closing (non-concussive), 15 mm to 25 mm (4) Valves, foot, of copper alloy not exceeding 51 mm (2 in.) of cast iron or steel of all types of seats (excluding leather flap type) sizes 51 mm to 305 mm (2 in. to 12 in.) (5) Valves, float, of brass or other copper alloy, not exceeding 153 mm (6 in.) (6) Valves, ball; (a) Screwed and weld end stainless steel and cast or barstock carbon steel bodies, 8 mm (¼ in.) to 80 mm (3 in.) B.S.P. and M.P.T. other than multiport and jacketed types (1) Screwed, brass, sizes 15 mm, 20 mm, 25 mm, 32 mm, 40 mm, and 50 mm B.S.P. (b) Valves ball (c) Screwed, cast iron, sizes 12 mm, 19 mm, 25 mm, 32 mm, 40 mm, 50 mm (d) Flanged, cast stainless steel or cast steel, sizes 50 mm (2 in.), 80 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.), tested fire safe (e) Screwed brass or bronze sizes; 8 mm (¼ in.) 10 mm (⅜ in.) 15 mm (½ in.) 20 mm (¾ in.) 25 mm (1 in.) with reduced bore and sizes 8 mm (¼ in.) 10 mm (⅜ in.) 15 mm (½ in.) 20 mm (¾ in.) with full bore (f) UPVC sizes 15 mm (½ in.) to 50 mm (2 in.) inclusive (7) Sluice or wedge gate (or stop) valves of cast iron and alloyed iron for waterworks purposes and like application, in nominal sizes 51 mm (2 in.) 76 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.), 200 mm (8 in.), 254 mm (10 in.), 300 mm (12 in.), 380 mm (15 in.), 400 mm (16 in.), 450 mm (18 in.), 500 mm (20 in.), and 600 mm (24 in.) double flange and spigot or socket ends, hand operated, for test pressures not exceeding 244 metres (800 ft.) head of water with or without copper based trims. In accordance with BSS 1218, NZSS 784, BSS 5163, and	Free	Free	..	202740C	1/83	6/86
							6/80	6/86
							3/83	6/86
							3/80	6/86
							8/80	6/86