Dated at Wellington this 8th day of March 1984 DENYS R. M. PINFOLD.	•	Number and Title of Specification	Price of Copy (Post free)
Director, Standards Association of New	Zealand.	Method 301.2:1978 Non-volatile content by	\$
(S.A. 114/2/12: 527-8)		volume (volume solids)	9.00
		Method 302.1:1975 Pigment content	4.50
		Method 401.1:1981 Surface dry condition Method 401.5:1980 Hard dry condition.	9.00
		Sanding test	4.50
		Method 401.6:1977 Hard dry condition (mechanical thumb test)	9.00
The Standards Act 1965—Overseas Specifications	s Endorsed as	Method 401.8:1981 No-pick-up time of road	7.00
Suitable for use in New Zealand		marking paints	9.00
PURSUANT to section 17 of the Standards Act 1965	the Standards	Method 402.1:1981 Bend test Method 403.1:1981 Scratch resistance	4.50 4.50
Council, on 24 February 1984, endorsed the u		Method 404.1:1981 Recoating properties	4.50
overseas specifications as suitable for use in New 2	Zealand.	Method 405.1:1978 Determination of pencil hardness of paint film	4.50
Number and Title of Specification	Price of Copy	Method 407.1:1981 Heat resistance. Slow	4.50
	(Post free)	cooling	4.50
Appita		Method 407.2:1981 Heat resistance. Thermal shock	4.50
P448s:1983 Tensile strength of paper and		Method 408.1:1974 Adhesion (paint inspection	
paperboard (constant rate of elongation method)	9.00	gauge) Method 408 2:1073 Determination of adhesion	9.00
AS 1580: Methods of test for paints and related	7.00	Method 408.2:1973 Determination of adhesion (knife test)	4.50
materials—	0.00	Method 408.3:1976 Adhesion (Arco	0.00
Method 101.1:1980 Air drying conditions Method 101.3:1980 Standard procedure for	9.00	microknife) Method 408.4:1980 Adhesion (cross-cut)	9.00 9.00
stoving	4.50	Method 452.1:1981 Resistance to humidity	
Method 101.4:1980 Conditions of test, temperature controlled	4.50	under condensation conditions	9.00
Method 101.5:1980 Conditions of test,	4.50	Method 452.2:1981 Resistance to corrosion- salt droplet test	9.00
temperature and humidity controlled	4.50	Method 453.1:1981 Resistance to petrolum	
Method 102.1:1980 Sampling procedure Method 103.1:1980 Preliminary examination	9.00	spirit Method 454.1:1982 Resistance to mineral oil	9.00 9.00
and preparation for testing	4.50	Method 455.1:1982 Resistance to mineral of	2.00
Method 104.1:1979 Recommended materials for test panels	4.50	room temperature	9.00
Method 105.1:1980 Pretreatment of metal test	4.50	Method 456.1:1975 Resistance to boiling water Method 457.1:1975 Resistance to outdoor	9.00
panels. Solvent cleaning	4.50	weathering	9.00
Method 105.2:1980 Pretreatment of metal test panels. Sanding	4.50	Method 458.1:1975 Resistance to wetting Method 459.1:1983 Resistance to washing	4.50 9.00
Method 105.3:1980 Pretreatment of metal test		Method 460.2:1982 Resistance to alkaline	9.00
panels. Chromic acid dipping Method 106.1:1979 Preparation of timber test	4.50	conditions (immersion test)	4.50
panels for outdoor weathering test	4.50	Method 461.1:1977 Determination of resistance to yellowing (dark chamber)	4.50
Method 107.1:1980 Determination of wet film	4.50	Method 481.1:1975 Assessment of individual	
thickness from dry film mass Method 107.2:1980 Determination of wet film	4.50	defects of exposed films Method 481.2:1975 Assessment of blistering	49.00
thickness from wet film mass	4.50	of paint films	26.50
Method 107.3:1980 Determination of wet film thickness by wheel gauge	9.00	Method 481.3:1975 Assessment of visible	22.00
Method 107.8:1979 Application of paint at a	7.00	rusting Method 481.4:1975 Assessment of corrosion	22.00
nominated spreading rate by determination	4.50	of an underlying iron or steel surface	4.50
of wet film mass (brush application) Method 108.1:1980 Determination of dry film	4.50	Method 481.5:1975 Determination of the durability, resistance to corrosion and	
thickness on iron and steel substrates	0.00	resistance to fouling of marine underwater	
(permanent magnet instruments) Method 202.1:1980 Density	9.00 9.00	paint systems Method 481 6:1075 Determinator of durability	4.50
Method 202.2:1980 Density of water dispersed		Method 481.6:1975 Determination of durability of marine underwater paint systems under	
paints subject to foaming Method 203.1:1980 Skin formation	4.50 4.50	cathodically protected conditions	4.50
Method 204.1:1977 Fineness of grind	9.00	Method 482.1:1975 Fastness to light Method 483.1:1973 Resistance to artificial	4.50
Method 205.1:1981 Application properties. Brushing	4.50	weathering (carbon-arc type instruments)	9.00
Method 205,2:1981 Application properties.		Method 501.1:1980 Soluble lead content (gravimetric method)	9.00
Conventional air spraying	4.50	Method 503.1:1973 Determination of water by	7.00
Method 205.3:1981 Application properties. Roller coating	4.50	the Dean and Stark method	4.50
Method 205.4:1981 Application properties.		Method 504.1:1979 Metallic zinc content Method 601.1:1975 Colour. Visual comparison	9.00 9.00
Airless spraying Method 208.1:1981 Thinning or mixing	4.50	Method 601.2:1975 Colour. Instrumental	
properties	4.50	measurement of colour difference using the 'Colormaster' differential colorimeter	9.00
Method 209.1:1975 Re-mixing properties Method 211.1:1980 Degree of settling	4.50 4.50	Method 601.3:1975 Colour. Instruments	
Method 211.2:1980 Ease of manual	4.50	measurement of colour difference using the	9.00
reincorporation	4.50	colour eye Method 602.1:1975 Visual assessment of gloss	4.50
Method 212.2:1981 Wet hiding power-Black and white chart brushout method	4.50	Method 602.2:1974 Specular gloss	9.00
Method 213.1:1981 Relative dry hiding power	9.00	Method 602.3:1974 Visual assessment of gloss (Boller)	4.50
Method 213.2:1975 Dry hiding power. Contrast ratio	9.00	Method 603.1:1975 Finish	4.50
Method 214.1:1975 Consistency of paints		Method 604.1:1973 45°, 0°. Reflectance of	4.50
measured by the Krebs-Stormer viscometer	9.00	white and pale coloured paints BS 3424: Testing coated fabrics—	4.30
Method 214.2:1975 Consistency-Flow cup Method 214.3:1978 Viscosity at a high rate of	9.00	Part 11:1982 Method 13. Method for	15.60
shear	9.00	determination of resistance to blocking Copies of the specifications may be ordered from	15.60 m the Standards
Method 215.1:1975 Levelling. Drawn-down method	13.00	Association of New Zealand, Wellington Trade	
Method 301.1:1975 Non-volatile content	4.50	Sturdee Street (or Private Bag), Wellington.	