THE NEW ZEALAND GAZETTE

Tariff Item	Description of Goods	Name and Address of Applicant	Part II Ref.	Appn. Ref. No.	*Category of Appn.
90.13.021	De Sisti professional studio lighting equipment	Maser Communications Ltd PO Box 65-166 3/7/ Marken Place Glenfield AUCKLAND	99	AK 500113H	A
90.24.011	Barksdale gold-line temperature switches series ML1H, ML1HO, MT1H, MT1H-RD, L1X, L2H, L2H-RD,T1X, T2H and T2H-RD	W Arthur Fisher Limited PO Box 12-747 Penrose AUCKLAND	••	DN 462162L	CA
90.24.011	Pneumatic transmissions: (1) Force balance, blind transmitters, with pneumatic output of 19.6kPa to 112.9kPa (2.84 to 16.39lbs per sq in.) Absolute pressure High range differential, pressure	W Arthur Fisher Limited PO Box 12-747 Penrose AUCKLAND		DN 462163J	CA
	Guage pressure Position Differential pressure, flow or liquid level Liquid level or density Repeater Vapour pressure				
	Speed Sanitary liquid level Flow transmitters Consistency (2) Pneumatic receiver-controller only, with				
	pneumatic imput signals of 19.6kPa to 112.9kPa (2.84 to 16.39lbs per sq in.) Pneumatic receiver indicating controllers Pneumatic receiver subpanels Pneumatic receiver control stations				
	Pneumatic receiver controllers for automatic control stations Pneumatic receiver batch and multiple auto- selector control Pneumatic receiver single case cascade control				
	systems Pnuematic receiver self-contained and gap action floating controllers Pneumatic receiver indicating/recording controllers				
	Pneumatic receiver auto-selector control system Pneumatic receiver indicating recording control stations Pneumatic receiver ratio controllers Pneumatic receiver computer compatible control systems				
	Computer set controller pulse-to-air converter Pneumatic receiver differential gap controller Pneumatic receiver single station cascade controller Pneumatic receiver auxilliary units				
*	Pneumatic receiver radio stations (3)Pneumatic receiver auxiliary instruments with pneumatic input signals of 19.6kPa to 112.9kPa (2.84 to 16.39lbs per sq.in.) Pneumatic receiver computing unit, air operated Pneumatic receiver integrator with some remote counter				
	Pneumatic receiver inegrator control system (4) Pressure transmitters only indicating and blind, with pneumatic output 19.6kPa to 112.9kPa (2.84 to 16.39lbs per sq.in.) pressure and relative humidity				
	 (5) Recorder to indicators, vertical or horizontal scales, with pneumatic imput signals of 19.6kPa to 112.9kPa (2.84 to 16.39lbs per sq.in.) (6) Pneumatic signal conditions with pneumatic output signals of 19.6kPa to 112.9kPa (2.84 to 16.39lbs per sq.in.) EMF, resistance or current input-to-pneumatic converters 				
	Current-to-air positioner (7) Mechanical programme type controllers, not being timers only Controller Set point transmitter				
	Cam set controller Time cam set point transmitter Elapsed time controller (8) Temperature, indicating and non-indicating, for use in industrial processors				
90.24.011	Temperature controllers, peculiar to use with plastic injection moulding machines	William H Terry & Co Ltd Private Bag Balmoral AUCKLAND	••	DN 462164G	CA
90.28.009	Analog devices, digital volt meter/thermometer, models AD2037 and AD2038	W Arthur Fisher Limited PO Box 12-747 Penrose AUCKLAND	99	DN 462165E	CA
90.28.009	Bailey controls electronic transmitters: (1) Solid state, flange mounted, level transmitter, type LQ (2) Solid state temperature transmitter, signal converter or millivolt converter, Type EQ	Bailey Controls Australia Pt PO Box 33251 Takapuna AUCKLAND	y Ltd 99	DN 462166C	CA
	(3) Electronic gauge and aboslute pressure transmitter, Type BQ9 and BQ6 (4) Solid state transmitter, Type BQ7 and BQ8 (5) Solid state pressure transmitter, Type KA				
90.28.009	Ircon brand of Infra-red non-contact Temperature measurement and Control Systems	Leeds & Northrup NZ Ltd PO Box 30248 LOWER HUTT		DN 462167A	CA