Tariff Industry Assistance (Decision)- Notice No. 1985/18 - cont'd

	Tariff Item	Description of Goods	Rates of Normal	Duty Pref.	Part II Ref.			ffective rom T	
0	84.61.021	Check valves (valves which prevent reversal of flow) viz; In line steel bodied check valves - over (3/4"),		Free			480756B	9/85	12/9
		Swing, tilting disc and dual plate: Brass, bronze or gunmetal bodies - 125mm (5") and above Iron or steel bodies 40mm ($1^{1}/_{2}$ ") and below							
		Iron or steel bodies - 900mm (36") and over							
		Stainless steel bodied - $40mm$ ($1^{1}/2$ ") and below Stainless steel bodied 500mm (20") and over							
		Plastic bodied - all sizes excluding aerosol types							
		Stainless steel bodied with flanged end connections - all si	zes						
		<u>Lift, globe or piston</u> : (Non Hydraulic) Aluminium bodied - all sizes							
		Brass, bronze or gunmetal bodied - 200mm (8") and above Cast iron, steel and stainless steel bodied - all sizes							
		Ball Check:							
		Cast iron, brass, bronze, gunmetal and plastic bodied (excluding aerosol types) - all sizes							
		Steel and stainless steel bodied - $40mm$ ($1^{1}/2$ ") and over Foot valves:							
		Cast iron, carbon steel or stainless steel bodied -							
		350mm (14") and over Brass, bronze or gunmetal bodied – $65mm$ ($2^{1}/2$ ") and over							
		Fisher G100 and G200 series Dorot back flow preventors							
		Apco silent check valves series 300 and 600, Factory Mutual approved							
0	84.61.021	Kitiza UO stainless steel swing check valve size 50mm Fire fighting equipment as may be approved;		Free			480766K	8/85	7/
		APPROVED:				•	100700K	0.00	
		Foam induction monitors and branch pipes; Nozzles for hoses peculiar to fire fighting (excluding nozzle							
		of plastic not exceeding 150mm (6")) having any or all of the following characteristics:	e						
		(a) a positive, variable gallonage flow selection;							
		(b) positive pre-selected discharge pattern control; (c) a flow rate greater than 2250 litres per minute							
N	84.61.021	"Keystone" model F793 pneumatic positioner to be used in		Free			461934L	8/85	9/
		conjunction with keystone pneumatic actuators for automatic acountrol of industrial valves	remote						
ſ		Intralox sprockets		Free	Free	10	461935J	7/85	9/
i (CR speedi-sleeves Tideland marine proof automatic battery chargers		Free	Free		420679H 401127K	4/85 6/85	6/
ì	85.03.001	Universal lighter battery model 10 x 28H		Free Free	Free Free		520151K	8/85	9/ 1/
i	85.12.019	Component parts peculiar to use in making domestic smoothing irons, shell "In the Rough" state		Free	Free	15	461937E	7/85	9/
i	85.12.019	Electric heating resistors for coffee warming trays		Free	Free	10	461938C	7/85	9/
1)		Intrinsically safe underground telephone systems Flourescent indicator panels, on condition that they are for		Free Free	Free		929353B 420789A	3/85 7/85	6/ 6/
		use solely in the manufacture of AM/FM high fidelity receiver	·s			• •	420/07A		
(85.17.000	Marine navigation beacons; Types;		Free	Free	10	401134B	4/85	9/
		Pharos PRB series, LBEA-85, LBEA-155, LBEA-250, LBEP-150, LBE	SP- 300						
N	85.19.009	PEB-85, LEBA-14, LETA-14, LEXA-14, LEXA-18 Components peculiar to use in making relays; Email relays.		Free	Free	15	461939A	7/85	9/
		models, IR, 3R, 6R, 12R, 13R, 21R, 25R, 26R, 2C720, 2P740,						.,	-
V	85.19.009	27149, 27249, 27749, 2V730, 2V731, ETP2, SFP1, STP and PLL1 Original miniature relays with a maximum contact rating 5 amp) S	Free	Free	10	461241J	8/85	9/
		resistance at 230V AC, models;	, ,				4012410	0,05	•
•	85.19.009	OUA, OUB, SRE, SRT, SRJ, SRZ, SRC, SRG, SMR, SRW and SRU Rotary switches for use in motor vehicle alternative fuel sys	t ome	Free	Free	10	401128H	3/85	9/
f	85.19.009	Starting relays for single phase CSR electric motors	, cems	Free	Free	10	420664K	7/85	6/
(I		Versa trak flat cable connectors Fixed wire wound resistors - 250 watt power rating		Free	Free Free	10	401129F 420631C	6/85 6/85	9/ 6/
V		Asea circuit board type QSDM 103% with meter panel and meter		Free Free	Free	10	560046E	9/85	6/
i	85.22.019	for use in the manufacture of metal detectors Westward brand, X-static ionizer solely for use in industrial	1	Free	Free	10	440136A	5/85	4/
		processes							
1	87.12.011	Cycle rims 317.5mm, 508mm, 609mm and 660.3mm wheel spokes and hubs, on condition that they are for use only in making inval		Free	Free	15	461942A	3/85	9/
ť	87.14.059	carriages Air sprung suspensions as may be approved - Neway suspensions	_		9		400050D	4 / O E	•
	07.14.037	on condition they are for use solely in the manufacture of	3	Free	Free	15	400958E	4/85	9/
ı	90.24.011	semi-trailers Sipair brand 3 pole, air compressor pressure controller		Fran			4403304	7 / 05	٠,
i	90.28.009	Digitron temperature measurement control equipment		Free Free	Free	10	440329A 461944H	7/85 7/85	6/ 9/
	90.28.009	Gow-Mac 21-252 gas leak detector		Free	Free	99		1/85	3/
	90.28.009	Leeds and Northrup range of electrical, measuring, checking, analysing and automatically controlling instruments and		Free	Free	99	461945F	7/85	9/
		apparatus, excluding those goods determined under Tariff							
ľ	91.08.000	item 90.28.001 Clock movements, on condition that they are incorporated		Free	Free	15	560080E	8/85	9/
	92 11 002	into New Zealand made clock surrounds							
	92.11.002	Office dictating machines and reproducers ancillary thereto, as may be approved;		Free		• •	461403J	7/85	9/
		APPROVED:							
ı		Olympus Pearlcorder L200							