THE NEW ZEALAND GAZETTE

SCHEDULE 1 General Decisions Approved - continued -

Tariff Item	Rates - Description of Goods	of Duly Pref	Part II . Ref.			Effectiv From T	-
48.19.000	Radiation detection pressure sensitive adhesive labels	Free	Free	99	4801870	5/85	3/86
48.19.000	Rotogravure printed label in widths greater than 400mm	Free	Free	15	4802630	1/85	6/92
48.19.000	Self adhesive labels used with automatic	Free	Free	99	4801888	5/85	12/85
	blood grouping machines) on condition that they are:						
	 Imported by a hospital board Imported solely for supply to hospital boards 						
48.20.001	Bobbins, reels, cones, cops and similar supports, peculiar to	Free	Free	99	480189L	5/85	9/85
	use in holding yarn during storage or processing						
	Spools, reels and similar supports designed for use with goods		Aul Free	33	4801900	5/85	12/86
	classified in Chapters 90 and 92, viz;						
	For photographic and cinematographic film	_	-			e /	
48.21.001	Patterns, on condition that they will be used by a manufacturer	Free	Free	15	480191B	5/85	9/92
49 21 010	solely as designs for making patterns for apparel Camera cards, dupli-cards and aperture cards peculiar to use in	Free	Free	99	480192L	5/85	3/86
40.21.019	micro filming systems	Free	rree	,,	4001920	27.02	3/00
48.21.019	Cardboard applicator tubes, peculiar to use with vaginal gel	Free	Free	99	480193J	5/85	9/86
	Cards, rectangular, plain or shallow perforated, coated with	Free	Free	15	480194G	5/85	3/86
	magnetic strips, on condition that they are solely for use in						
	making printed ledger cards			_			
48.21.019	Creped paper tubes and resin bonded tubes on condition that they are	e Free	Free	15	480195E	5/85	9/92
	solely for use in making or repairing transformers	-	-			· - /ar	~ / ~ ~
48.21.019	Evaporative cooling media in fluted cellulose pad form on	Free	Free	99	480196C	5/85	9/92
48 21 010	condition it is solely for use in horticultural applications Filter paper articles for laboratory use	Free	Free	99	480197A	5/85	9/86
	Gaskets, single orifice, other than circular, whether plain or	Free	Free	99	480197H		9/86
	holed for bolts						.,
48.21.019	Heat sealable sterilisation packaging materials comprising a	Free	Free	99	480199H	5/85	9/92
	paper base with a transparent film laminate fixed to it on two						
	edges to steriliser tubing, on condition for use in sterilisation						
	Holders especially designed to hold x-ray films in the mouth	Free	Free	99	480200E		3/86
48.21.019	Industrial wipes on condition they are used solely for the cleaning	Free	Free	99	480201C	5/85	6/86
49 21 010	of printing plates Materials for use in inisting electric cables	Free	Free	99	480202A	5/85	9/91
	Materials for use in jointing electric cables Paster tabs, for splicing reels of newsprint	Free	Free	15	480203K		9/90
	Readymounts, being frames incorporating an electronic seal insert	Free	Free	15	480204H		9/90
	for mounting colour transparencies			-			
48.21.019	Recording paper and tapes on condition that they are for use	Free	Free	99	480205F	5/85	9/86
	solely with measuring and testing instruments and apparatus						
	Rods and sticks, solid, of circular cross-section		Aul Free	33	480206D		12/87
48.21.019	Rolled sprocket punched recording paper peculiar for use with	Free	Free	99	480207B	5/85	3/86
	computer controlled pattern marker	_	-	~~			0.000
	Self adhesive or premoistened electrode patches	Free	Free	99 99	480208L 480209J		9/86 3/86
	Sliver cans of fibreboard Silver estimating test papers	Free Free	Free Free	99	4802108		9/86
	Woven enka material, 100% polyester	Free	Free		480418L		6/87
	Woven nylon taffeta fabric	Free	Free	15	480419J		6/90
	Taffeta sewn to a compressed backing;	Free	Free	99	4804208	7/85	6/90
51.04.028)	(1) in widths not exceeding 46cm; or						
	(2) when declared by a manufacturer for use by him only in						
o i (50	making hats	~	F		4605001	E /0E	6 (00
Chapter 59	Fabrics, combined with rubber sheet assembled in layers and fabrics	Free	Free	15	460590L	5/85	6/93
	coated with rubber which are impermeable to water (not including adhesive fabric)						
59.03.001		Free	Free	15	931832B	1/85	6/87
	Dyed nylon taffeta coated on one side only with PVC for use	Free			931277D		9/93
	in the manufacture of airways travel bags						
60.01.022	Nylon dress net produced by knitting processes	Free	Free	15	480399L	7/80	9/86
60.05.179		Free	Free	15	931410F	2/85	9/93
69.13.001		Free	Free	15	480401F	1/85	9/89
	will be used solely in the manufacture of high quality						
70.19.009	miniature wases Crystal decorative small wares on condition that the goods are	Free	Free	15	931290A	3/85	9/93
	for use in the making of household ornaments and imitation					5, 65	2,00
	iewellerv only						
70.20.061	Double bias fibreglass fabric in widths exceeding one metre,	Free	Free	99	931284G	10/84	9/93
	on condition that it will be used solely in the manufacture						
	of fibreglass laminates						
	T.B.A. woven glass fibre cloth for thermal insulation	Free	Free		931261H	2/85	3/93
70.20.081	Rectangular hollow sections, drawn after welding to eliminate	5%	Aul Free	99	931412B	2/85	9/93
70.20.081 73.18.009							
	internal seam, in following sizes only:						
	68mm x 68mm x 4.7mm wall thickness						
	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods						6/93
	68mm x 68mm x 4.7mm wall thickness	5	Aul Free	99	460438H	4/85	
73.18.009	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods will be used solely in the making of duro torque axle assemblies	5 Free	Aul Free	99 	460438H 460437H	4/85 4/85	6/93
73.18.009 73.18.009	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods will be used solely in the making of duro torque axle assemblies Welded steel conduit, peculiar to use in electrical wiring work Conduit pipe and pipe fittings Fire rated doors and fittings for Wilkinson Chutes only		Aul Free Free				6/93 9/93
73.18.009 73.18.009 73.20.001 73.21.000 73.25.009	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods will be used solely in the making of duro torque axle assemblies Welded steel conduit, peculiar to use in electrical wiring work Conduit pipe and pipe fittings Fire rated doors and fittings for Wilkinson Chutes only High tensile steel 7 wire strand 9.3mm to 9.6mm, 11.0mm to 11.3mm	Free Free Free	Free	 99 99	460437H 931286C 931283J	4/85 3/85 12/84	6/93 9/93 9/93
73.18.009 73.18.009 73.20.001 73.21.000	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods will be used solely in the making of duro torque axle assemblies Welded steel conduit, peculiar to use in electrical wiring work Conduit pipe and pipe fittings Fire rated doors and fittings for Wilkinson Chutes only High tensile steel 7 wire strand 9.3mm to 9.6mm, 11.0mm to 11.3mm Copper tube to ASIM B88, special hardness 60-75 VPn for the	Free Free	Free	 99	460437H 931286C	4/85 3/85	6/93 9/93
73.18.009 73.18.009 73.20.001 73.21.000 73.25.009 74.07.009	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods will be used solely in the making of duro torque axle assemblies Welded steel conduit, peculiar to use in electrical wiring work Conduit pipe and pipe fittings Fire rated doors and fittings for Wilkinson Chutes only High tensile steel 7 wire strand 9.3mm to 9.6mm, 11.0mm to 11.3mm Copper tube to ASIM 880, special hardness 60-75 VPn for the manufacture of low-fin copper tube	Free Free Free Free	Free Free Free	99 99 99	460437H 931286C 931283J 931281B	4/85 3/85 12/84 11/84	6/93 9/93 9/93 9/93
73.18.009 73.18.009 73.20.001 73.21.000 73.25.009 74.07.009 76.02.001	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods will be used solely in the making of duro torque axle assemblies Welded steel conduit, peculiar to use in electrical wiring work Conduit pipe and pipe fittings Fire rated doors and fittings for Wilkinson Chutes only High tensile steel 7 wire strand 9.3mm to 9.6mm, 11.0mm to 11.3mm Copper tube to ASIM B88, special hardness 60-75 VPn for the manufacture of low-fin copper tube Aluminium formed wire, type 110C-3 in coil form	Free Free Free Free Free	Free Free Free Free	99 99 99 99	460437H 931286C 931283J 931281B 460429G	4/85 3/85 12/84 11/84 4/85	6/93 9/93 9/93 9/93 9/93
73.18.009 73.18.009 73.20.001 73.21.000 73.25.009 74.07.009 	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods will be used solely in the making of duro torque axle assemblies Welded steel conduit, peculiar to use in electrical wiring work Conduit pipe and pipe fittings Fire rated doors and fittings for Wilkinson Chutes only High tensile steel 7 wire strand 9.3mm to 9.6mm, 11.0mm to 11.3mm Copper tube to ASIM 888, special hardness 60-75 VPn for the manufacture of low-fin copper tube Aluminium formed wire, type 110C-3 in coil form Cooling discs to prevent hot air being drawn into air supply fans	Free Free Free Free Free Free	Free Free Free Free Free	99 99 99 15	460437H 931286C 931283J 931281B 460429G 931278B	4/85 3/85 12/84 11/84 4/85 2/85	6/93 9/93 9/93 9/93 6/93 9/93
73.18.009 73.18.009 73.20.001 73.21.000 73.25.009 74.07.009 76.02.001 76.16.059 82.09.011	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods will be used solely in the making of duro torque axle assemblies Welded steel conduit, peculiar to use in electrical wiring work Conduit pipe and pipe fittings Fire rated doors and fittings for Wilkinson Chutes only High tensile steel 7 wire strand 9.3mm to 9.6mm, 11.0mm to 11.3mm Copper tube to ASIM B80, special hardness 60-75 VPn for the manufacture of low-fin copper tube Aluminium formed wire, type 110C-3 in coil form Cooling discs to prevent hot air being drawn into air supply fans Wiltshire staysharp knife blades	Free Free Free Free Free Free Free	Free Free Free Free Free Free	99 99 99 15 15 99	460437H 931286C 931283J 931281B 460429G 931278B 460430L	4/85 3/85 12/84 11/84 4/85 2/85 4/85	6/93 9/93 9/93 9/93 6/93 6/93 6/93
73.18.009 73.18.009 73.20.001 73.21.000 73.25.009 74.07.009 76.02.001 76.16.059 82.09.011	68mm x 68mm x 4.7mm wall thickness 56mm x 56mm x 3.6mm wall thickness on condition that the goods will be used solely in the making of duro torque axle assemblies Welded steel conduit, peculiar to use in electrical wiring work Conduit pipe and pipe fittings Fire rated doors and fittings for Wilkinson Chutes only High tensile steel 7 wire strand 9.3mm to 9.6mm, 11.0mm to 11.3mm Copper tube to ASIM 888, special hardness 60-75 VPn for the manufacture of low-fin copper tube Aluminium formed wire, type 110C-3 in coil form Cooling discs to prevent hot air being drawn into air supply fans	Free Free Free Free Free Free	Free Free Free Free Free	99 99 99 15	460437H 931286C 931283J 931281B 460429G 931278B 460430L	4/85 3/85 12/84 11/84 4/85 2/85 4/85	6/93 9/93 9/93 9/93 6/93 6/93 6/93