## 3062

## THE NEW ZEALAND GAZETTE

No. 111

(

Tariff Industry Assistance (Decision) Notice No. 1986/27-continued

| Tariff<br>Item          | Description of Goods  | Rates of<br>Normal | Duty<br>Pref. | Part<br>II<br>Ref. | Ref.<br>No. | Effect:<br>From | ive<br>To |
|-------------------------|---|--------------------|---------------|--------------------|-------------|-----------------|-----------|
|                         | (b) Expanded metal from 0.4mm to 4mm thickness, from 1mm  |                    |               |                    |             |                 |           |
|                         | S.W.M. to 38mm S.W.M., including flattened mesh, but not  |                    |               |                    |             |                 |           |
|                         | anodised  | Enco               | Enco          | 00                 | 501004F     | 7/96            |           |
| 82.02.028<br>Whole Item | Saws (non-mechanical) and blades for hand or machine saws (including toothless saw blades):                                       | Free               | Free          | 99                 | 561334F     | 7/86            | ••        |
|                         | Other blades:   |                    |               |                    |             |                 |           |
|                         | Other kinds:  |                    |               |                    |             |                 |           |
|                         | EXCLUDING:<br>(1) tungsten carbide tipped   |                    |               |                    |             |                 |           |
|                         | (2) solid tooth from 305mm (12in) to 610mm (24in) diameter,   |                    |               |                    |             |                 |           |
|                         | designed for cutting timber   |                    |               |                    |             |                 |           |
|                         | Gang saw blades for wood sawing<br>High carbon steel bandsaw blade (excluding high speed  |                    |               |                    |             |                 |           |
|                         | steel solid and high speed steel welded edge, and   |                    |               |                    |             |                 |           |
|                         | tungsten carbide tipped and tungsten carbide coated)  |                    |               |                    |             |                 |           |
|                         | for cutting meat, bone, metal and wood in<br>(i) Hard edge flexible back; or  |                    |               |                    |             |                 |           |
|                         | (ii) Hard edge tempered (i.e. toughened) back types, in   |                    |               |                    |             |                 |           |
|                         | any length, and of the following dimensions:  |                    |               |                    |             |                 |           |
|                         | (a) in widths between 6.35mm and 31.75mm inclusive; and   |                    |               |                    |             |                 |           |
|                         | (b) with pitches between 3 and 32 teeth per 25.40mm, excluding scalloped teeth  |                    |               |                    |             |                 |           |
|                         | Jigsaw blades   |                    |               |                    |             |                 |           |
|                         | EXCLUDING:  |                    |               |                    |             |                 |           |
|                         | Blades over 80mm in total length;<br>Lugged typed blades;   |                    |               |                    |             |                 |           |
|                         | Tungsten carbide coated and tipped blades   |                    |               |                    |             |                 |           |
|                         | High speed, hollow ground side clearance types or ground  |                    |               |                    |             |                 |           |
| 82.05.018               | tooth form types<br>Countersinks - single flute, 1/2 shank 15.5 - 19.5mm,   | Free               | Free          | 99                 | 679715G     | 7/86            |           |
|                         | on condition that they are used solely by a manufacturer  |                    |               |                    |             |                 |           |
| 00.05.010               | in the metal working industry   | Enee               | Ence          | 00                 | 6707165     | 7/00            |           |
| 82.05.018               | Drills - tungsten carbide tipped metal working, twist<br>from 2.381, on condition that they are used solely by                    | Free               | Free          | 99                 | 679716E     | 7/86            | ••        |
|                         | a manufacturer in the metal working industry  |                    |               |                    |             |                 |           |
| 82.05.018               | Facing cutters, tungsten carbide tipped, circular;  | Free               | Free          | 99                 | 679717C     | 7/86            | ••        |
|                         | other than throwaway tip types, on condition that they<br>are used by a manufacturer in the metal working industry                |                    |               |                    |             |                 |           |
| 82.05.018               | Interchangeable tools for hand tools, for machine tools   | Free               | Free          | 99                 | 561335D     | 7/86            | ••        |
|                         | or for power-operated hand tools (for example, for  |                    |               |                    |             |                 |           |
|                         | pressing, stamping, drilling, tapping, threading, boring,<br>broaching, milling, cutting, turning, dressing, morticing            |                    |               |                    |             |                 |           |
|                         | or screw driving), including dies for wire drawing,   |                    |               |                    |             |                 |           |
|                         | extrusion dies for metal, and rock drilling bits:   |                    |               |                    |             |                 |           |
|                         | OTHER KINDS:<br>EXCLUDING:  |                    |               |                    |             |                 |           |
|                         | (1) Drills  |                    |               |                    |             |                 |           |
|                         | (a) HSS and carbon/chrome/vanadium/tungsten steels,   |                    |               |                    |             |                 |           |
|                         | right hand helix;-  |                    |               |                    |             |                 |           |
|                         | (i) Straight shank Jobber length, double and single<br>ended stub length and long series length lmm                               |                    |               |                    |             |                 |           |
|                         | to 13mm (3/4in. to 1/2in.)  |                    |               |                    |             |                 |           |
|                         | (ii) Straight shank long reach length 3mm   |                    |               |                    |             |                 |           |
|                         | to 13mm (1/8in. to 1/2in.)<br>(iii) Reduce shank of any diameter including Blacksmith   |                    |               |                    |             |                 |           |
|                         | type 13mm to 32mm (33/64in. to 1 1/4in.)  |                    |               |                    |             |                 |           |
|                         | (iv) Reduced shank of any diameter (metal and wood-   |                    |               |                    |             |                 |           |
|                         | working) with standard or dowelling bit point<br>6mm to 13mm (1/4in. to 1/2in.)   |                    |               |                    |             |                 |           |
|                         | (v) Straight shank (4 flute core type) 3mm  |                    |               |                    |             |                 |           |
|                         | to 13mm (1/8in. to 1/2in.)  |                    |               |                    |             |                 |           |
|                         | <ul><li>(b) Tungsten carbide tipped twist from 2.381mm</li><li>(c) Drill sets, containing above type drills in diameter</li></ul> |                    |               |                    |             |                 |           |
|                         | ranges;   |                    |               |                    |             |                 |           |
|                         | Straight shank;   |                    |               |                    |             |                 |           |
|                         | 1mm to 13mm<br>1/16in. to 1/2in.  |                    |               |                    |             |                 |           |
|                         | Reduced shank;  |                    |               |                    |             |                 |           |
|                         | 6mm to 20mm   |                    |               |                    |             |                 |           |
|                         | <ul><li>1/4in. to 3/4in.</li><li>(d) Tungsten carbide tipped masonry, drills straight</li></ul>                                   |                    |               |                    |             |                 |           |
|                         | also reduced shank of any shank diameter "short"  |                    |               |                    |             |                 |           |
|                         | or ''long'' overall lengths within diameter range;  |                    |               |                    |             |                 |           |
|                         | 3mm to 32mm;<br>1/8in. to 1 1/4in.  |                    |               |                    |             |                 |           |
|                         | (e) Countersinks, single flute;   |                    |               |                    |             |                 |           |
|                         | 1/2in. shank 15.5mm to 19.5mm   |                    |               |                    |             |                 |           |
|                         | (f) Reamers, Parallel Machine, Tungsten Carbide   |                    |               |                    |             |                 |           |
|                         | tipped, non-adjustable;<br>straight shank, all sizes under 14.29mm morse  |                    |               |                    |             |                 |           |
|                         |   |                    |               |                    |             |                 |           |