## THE NEW ZEALAND GAZETTE

 $Tariff\ Industry\ Assistance\ (Advertisement)\ Notice\ No.\ 1986/29-continued$ 

Tariff Item	Description of Goods	Name and Address of Applicant	Part II Ref.	Appn. Ref. No.	*Category of Appn.
	Tower refrigeration rubber bellows			HO 210134D	VA
40.09.031	CURRENT APPROVAL			210135B	WA
	Rubber bitumen hoses, when declared for use with bitumen at 150oC, reinforced carcass,		• •	2101358	VA
	outer cover ageing/abrasion/ weathering/oil				
	resistant C/W ANSI 150 weld-neck flanges				
	electrically bonded REQUESTED APPROVAL				
40.03.031	Rubber bitumen hoise viz:			HO 210135B	VA
	Reinforced carcass, outer cover ageing/				
	abrasion/ weathering/oil resistant C/W ANSI				
40.09.031	150 weld-neck flanges electrically bonded CURRENT APPROVAL				
	Rubber pigtails, peculiar for use in		• •	210136L	VA
	installations of liquid petroleum gas				
40.09.031	cylinders REQUESTED APPROVAL				
	L.P.G. gas cylinder rubber pigtails		• •	HO 210136L	VA
40.09.031	CURRENT APPROVAL				
	Rubber rein grip tubing on condition that it will be used solely in the manufacture of		• •	930721E	VA
	non slip reins				
40.09.031	REQUESTED APPROVAL				
	Rein grip tubing		• •	HO 930721E	VA
40.09.031	CURRENT APPROVAL Submarine or flotation hose of 152 mm diameter			500430G	VA
	or larger, in lengths greater than 3.05 M on		••	0001000	***
	condition that it will be used solely for				
	pumping ironsand slurry				
	REQUESTED APPROVAL  Ironsand slurry Submarine or flotation hose of			HO 500430G	VA
	152 mm diameter or larger, in lengths greater				
	than 3.05 M				
40.09.031	CURRENT APPROVAL Super Ortac hose, reinforced with braided wire,	•		210138G	VA
	for use in pumping hot fats		• •	2101380	VA.
40.09.031	REQUESTED APPROVAL				
40.09.031	Super Ortac hose, reinforced with braided wire, CURRENT APPROVAL		• •	HO 210138G	VA
-5.55.551	Togawa rubber high pressure hydraulic hose,			210139E	VA
	sizes 15.9mm, 19mm which meets or exceeds			222200	
	requirements Sae 100 RIA, for use only preset				
40.09.031	petrol pumps REQUESTED APPROVAL				
	Petrol pump high pressure hydraulic hose,			HO 210139E	VA
	sizes 15.9mm, 19mm which meets or excees				
40.09.031	requirements Sae 100 RIA CURRENT APPROVAL				
	Trelleborg trellheat hose, only for use as a			210140J	VA
	furnace door closing heat resistance to				
	400oc is required REQUESTED APPROVAL				
	Trelleborg trellheat hose, with heat resistant			HO 210140J	VA
	to 400oc				
40.09.031	CURRENT APPROVAL Wire braided water and radiator hose, sizes			2101425	\$7A
	12mm to 150mm inside diameter for use with		••	210142E	VA
	Detroit diesel engines				
40.09.031	REQUESTED APPROVAL			WO 010140F	•••
	Diesel engine wire braided water and radiator hose, sizes 12mm to 150mm		••	HO 210142E	VA
40.09.031	CURRENT APPROVAL				
	6mm ID rubber dual line 0 x 7 and acetylene		• •	501233D	VA
	welding hoses on condition that it is used in the arc welding trade				
40.09.031	REQUESTED APPROVAL				
	Acetylene/arc welding hose, 6mm ID rubber dual		• •	HO 501233D	VA
40.09.039	line 0 x 7 CURRENT APPROVAL				
10.03.033	Ammonia suction hose being 1'' I D wrapped		99	520521C	VA
	synthetic rubber and canvas hose used as				
	replacement hoses for birds eye model E30 plate frosters				
40.09.039 40.09.039	REQUESTED APPROVAL				
	Ammonia suction hose being 25.4mm I D wrapped		99	HO 520521C	VA
	synthetic rubber and canvas hose CURRENT APPROVAL				
	Reinforced synthetic rubber seal tube for use		99	420287C	VA
	in sealing floating roof tanks				- -
40.09.039	REQUESTED APPROVAL Floating roof tank reinforced synthetic		00	UO 4202070	WA
	rubber seal tube		99	HO 420287C	VA
40.09.041	CURRENT APPROVAL				
	Closed cell nitrile rubber piping, on		99	501897J	VA