THE NEW ZEALAND GAZETTE

Tariff Industry Assistance (Advertisement) Notice No. 1986/39-continued

Tariff Item	Description of Goods	Name and Address of Applicant	Part II Ref.	Appn. Ref. No.	*Category of Appn.
		PO Box 51-427 Pukuranga			
85.19.052	Plug couplers, 120w for cable termination equipment	AUCKLAND 6 Director Purchasing & Supply Branch New Zealand Railways Corporation Private Bag WELLINGTON	99	WN 620380	A
85.19.052	CURRENT APPROVAL	*LELINGION			
	Sockets, and plugs therfor, wire and cable connectors andthe like EXCLUDING: (1)Aluminium compression fittings, peculiar for use in jointing and terminating aluminium wire	Comptroller of Customs Private Bag WELLINGTON	99	HO 561362A	VA
	and cable EXCLUDING: Fittings when declared by a manufactured for use				
	on; (a) Three core sector cable (b) Four core sector cable exceeding 185mm+cross-				
	 (a) Four costs section cable exceeding roommercloss- sectional area (2)Battery isolaters, peculiar for use on all types of storage batteries including automative and 	S			
	marine batteries (3)Co-axial plugs, car radios type (4)Industrial and protected type plugs, sockets, cable couplers, appliance inlets and switch socket; rated 110 to 415 volts and up to 63 amps;	S			
	EXCLUDING: Aluminium clad industrial plugs, sockets cable couplers, appliances inlets and switch sockets with maximum voltage rating of 500 V AC/DC, from				
	16-63 amps continous rated current, flat formation (i.e. round pins in a straight line) pin/socket configuration				
	 (5)Plugs, sockets, tap-ons, cord extension sockets 250 volts, 15 amp maximum rating (6)Split bolt, bolt on type overhead line tap connectors suitable for tap connections on 	,			
	copper lines, having overall diameters from 2.74mm to 14.76mm (0.108in to 0.58lin) and split bolt, bolt on type cover head line				
	tap connectors suitable for tap connections on aluminium lines having overall diameters from 6.35mm to 14.61mm (0.250in to 0.575in) (7)Trailer plugs and sockets, viz;				
	4 pole, 5 pole and 7 pole (8)Wire and cable ring tingue connecting lugs crimp type, uninsulated, for conductors up to 185mm+in cross-sectional area EXCLUDING:				
	Compression type jointing sleeves, peculiar for use in jointing soild copper, stranded copper and copper coated conductors, used in telecommuncation and power line wires				
85.19.052	(9)Wire connectors in strips REQUESTED APPROVAL Sockets, and plugs therfor, wire and cable		99	HO 505811C	A
	connectors andthe like EXCLUDING: (1)Aluminium compression fittings, peculiar for				
	use in jointing and terminating aluminium wire and cable EXCLUDING: Fittings when declared by a manufactured for use				
	 (a) Three core sector cable (b) Four core sector cable exceeding 185mm+cross- 				
	sectional area (2)Battery isolaters, peculiar for use on all types of storage batteries including automative and	3			
	<pre>marine batteries (3)Co-axial plugs, car radios type (4)Industrial and protected type plugs, sockets, cable couplers, appliance inlets and switch sockets rated 110 to 415 volts and up to 63 amps;</pre>	3			
	EXCLUDING: (a)Aluminium clad industrial plugs, sockets cable couplers, appliances inlets and switch sockets				
	with maximum voltage rating of 500 V AC/DC, from 16-63 amps continous rated current, flat formation (i.e. round pins in a straight line) pin/socket configuration				

.