THE NEW ZEALAND GAZETTE

Tariff Industry Assistance (Decision) Notice No. 1985/36-contined

| | Tariff Item | Description of Goods | Rates o Normal | f Duty Pref. | Part II Ref. | Ref. No. | Effect From | | |
|--------|--------------------------|--|-------------------|-----------------|--------------------|--------------------|----------------|---------------|--|
| N | 39.07.599 | Components of solare window blinds and micro blinds, as may be approved | Free | Free | 15 | 520386E | 7/85 | 7/90 | |
| Н | 40.08.032 | Styrene butadiene foam rubber sheet or ring | Free | | | 540497F | 11/85 | 9/90 | |
| 1 | | T D Williamson type U and Z casing seal | Free | | •• | 560872E | | 3/94 | |
| ٧ | 42.04.001 | Round leather belts, peculiar to use with Industrial | Free | Free | 99 | 560842C | 10/85 | 3/94 | |
| | | Sewing Machines, 8 mm and 9.5 mm | | _ | | | | | |
|) | | Seed germinating paper | Free | Free | 99 | 580528H | | | |
|) | 48.01.129 | Linson unembossed or plain bookbinding paper and Kendal unembossed or plain covering paper, on condition for use solely in covering books | Free | Free | 99 | 580757D | 11/85 | 12/90 | |
| 0 | 56.07.034) 56.07.036) | Textile fabric laminated to cardboard | Free | Free | 15 | 502187B | 11/85 | 9/89 | |
|) | | HY-E type graphite (continuous) derived from poly a crylonitrile | Free | Free | 99 | 501859F | 1/86 | 9/89 | |
|) | | Deep pile silver knitted fabric with pile length of 8mm or more or weighing not less than 400 g.s.m. | Free | Free | 15 | 502684K | 11/85 | 9/89 | |
| N | | Jet pipe freezer packs | Free | Free | 99 | 560844K | 10/85 | 3/94 | |
| N | | Glass stones unmounted | Free | Free | 15 | 560776H | | 12/93 | |
| N | 70.20.081 | Clark schwebel woven fibreglass fabric | Free | Free | 15 | 560847D | | 3/94 | |
| N | | ''Presbrite'' chrome plated steel strip | Free | Free | 15 | 560877F | 7/85 | 3/94 | |
| 0 | | High tensile and alloy wire to withstand corrosion, abrasion and weight | 5 | Free | 99 | 501636D | | 9/89 | |
| N | 73.20.021 | ''Grayloc'' connectors, mechanical connectors for pipes and vessels | Free | | •• | 560849L | 12/85 | 3/94 | |
| N · | 73.20.059 | Isolating joints 1/2'' to 60'' diameter with a pressure rating up to ANSI 2500 for a product temperature in the range of 500-280oC | Free | Free | 99 | 520878F | 11/85 | 11/90 | |
| N. | 73.40.069 | Quick opening hinged closures, class 600 to ASME VIII | Free | Free | 15 | 520852B | 11/85 | 11/90 | |
| N | 73.40.069 | • | Free | Free | 15 | 520853L | 11/85 | 11/90 | |
| | | bore, class 600 to BS5500 for sealing of Kingtool pressure vessels | | | | | | | |
| 0 | 74.19.009 | •• | Free | Free | 99 | 501396J | 8/85 | 9/89 | |
| H N | 76.03.011 76.10.021 | Aluminium bottles, 1 litre capacity complete with tamper | Free Free | Free | 99 | 540408J 520893K | 10/85 1/86 | 9/93 1/91 | |
| N | 76.10.029 | proof stoppers for packaging of dangerous goods Aluminium bottles, 2.5 litre capacity complete with tamper proof stoppers for packaging of dangerous goods | Free | Free | 99 | 520889A | 1/86 | 1/91 | |
| 0 | 76.16.041 | Harken furling systems | Free | Free | 15 | 501575J | 8/85 | 9/89 | |
| N | 81.04.019 | | Free | Free | 15 | 560851B | 10/85 | 3/94 | |
| 0 | 82.04.011 | Screwdrivers with plastic handles with straight fixed blades within the following dimensions, for slotted head screws -3.63 mm (1/7 in) to 11.11 mm (7/16 in) | Free | | •• " | 501114A | 8/85 | 9/89 | |
| | | diameter blades of a length between 38.1 mm | | | | | | | |
| | | (1 1/2 in) and 355 mm (14 in), also Phillips and | | | | | | | |
| | | Pozidrive screwdrivers in sizes 0, 1, and 2 in lengths between 38.1 mm (1 1/2 in) and 152.4 mm (6 in) and | | | | | | | |
| | | sizes 3 and 4 in lengths between 152.4 mm (6 in) and 203.2 mm (8 in); | | | | | | | |
| | | EXCLUDING: | | | | | | | |
| | | (A) Screwdrivers for screwheads other than slotted, | | | | | | | |
| | | Phillips and Pozidrive (B) screwdrivers with devices to hold the screw, while | | | | | | | |
| | | starting it | | | | | | | |
| | | (C) Screwdrivers made from non-sparking metals | | | | | | | |
| | | (D) Screwdrivers with insulated shafts, other than 4.77 mm (3/16 in) diameter | | | | | | | |
| | | (E) Blades and blanks on condition that they will be used only in the manufacture of screwdrivers | | | | | | | |
| 10 | 82.04.079 | | Free | Free | 99 | 501724G | 10/85 | 9/89 | |
| N | 82.05.019 | | Free | Free | 99 | 560852L | | 3/94 | |
| N | 83.02.029 | Base metal fittings and mountings for solare window blinds and micro blinds as may be approved | Free | Free | 15 | 520387C | 7/85 | 7/90 | |
| Н | 83.02.029 | | Free | Free | 15 | 540420H | 11/85 | 9/93 | |
| N | 83.05.009 | | Free | Free | 15 | 560853J | 10/85 | 3/94 | |
| H | 83.14.000 | | Free | Free | 15 | 540417H | 10/85 | 9/93 | |
| | 84.06.021 | Water cooled engines, as may be approved; APPROVED: | Free | | . • • | | | | |
| N | | Gardner watercooled marine propulsion engines, models 6LXB, 8LXB, 8L3B, 6LXCT and 8LXCT | | | | 560854G | 12/85 | 3/94 | |
| N H | 84.10.029 | Lister blackstone marine engine, model 4JW6 Agitor ink pumping system model H53 for flexigraphic | Free | Free | 10 | 560878D 540411J | 7/85 9/85 | 12/93 8/87 | |
| 0 | 84.11.041 | printing press Compressor outfits, other than vehicle drawn; | Free | Free | 10 | 580756F | 11/85 | 6/88 | |
| | | EXCLUDING: (1) Reciprocating types with a piston displacement from | | | | | | | |
| | | .94 litres/second up to 26 litres/second (inclusive), with working pressures up to 1100 kPa | | | | | | | |
| | | (2) Reciprocating types with a piston displacement from | | | | | | | |
| | | 20 litres/second up to 200 litres/second (inclusive), | | | | | | | |
| | | 20 litres/second up to 200 litres/second (inclusive), with working pressures from 13,750 kPa and above | | | | | | | |