Tariff Industry Assistance (Decision) Notice No. 1986/15-continued

	Tariff Item	Description of Goods	Rates of Normal	f Duty Pref.	Part II Ref.	Ref. No.	Effect From	ive To	
	84.22.009	Bottle elevator/lowerator conveyor consisting of	Free	Free	10	503891L	12/85		
		parallel plate chains with rubber grippers capable of transporting between them a range of empty or	1100	1100		0000012	12,00	••	
		full bottle diameters							
	84.22.009	. •	Free	Free	10	521618E	2/86		
	84.22.009		Free	Free	15	521575H	2/86	• •	
	84.22.009	Pan and tilt heads and static mounting platforms	Free	Free	99	521480H	2/86		
		for the mounting of security and surveillance closed circuit cameras							
	84.22.009	Scissor gearkit C/W wide spread jacks and bridge hydraulics	Free	Free	10	521584G	2/86	••	
	84.22.009	• • • • • • • • • • • • • • • • • • • •	Free	Free	15	505061J	10/85	• •	
	84.23.011	Wheeled front end loaders, (excluding track types)	35	Aul 5		581621B	5/86	12/86	
	Deter'n	whether or not assembled, as defined by SAE Standard		Can 25					
		SAE J1057 (published in the Society of Automotive		Pac Free					
		Engineers, Inc Handbook) which cannot rotate through							
		the horizontal plane without movement of the wheels							
		with a static tipping load in full turn capacity up							
		to and including 16,000kg as measured to SAE							
		Standard J732c							
		This measurement shall be applied to these loaders							
		equipped to the Manufacturers' worldwide official							
		specifications excluding tyre ballast and optional							
		counterweights							
	84.23.011		35	Can 25		581622L	1/87		
	Deter'n	whether or not assembled, as defined by SAE		Aul Free	-				
	D0101	Standard SAE J1057 (published in the Society of		Pac Free					
		Automotive Engineers, Inc Handbook) which cannot		140 1100					
		rotate through the horizontal plane without movement							
		of the wheels with a static tipping load in full							
		turn capacity up to and including 16,000							
		kg as measured to SAE Standard J732c This							
		measurement shall be applied to these loaders							
		equipped to the manufacturers' worldwide official							
		specifications excluding tyre ballast and optional							
		counterweights							
	84 23 079	Crane attachment drilling machine	Free	Freel	10	521514F	2/86		
		Componentry for the manufacture of reversible	Free	Free	99	540559K	1/86		
		ploughs viz:	1100		00	0.1000011	1,00	• •	
	01.21.021)	Mouldboards - left and righthand headstock							
		turnover assembly dowdeswell patented 6 ball							
		auto release system							
	84.30.029	· · · · · · · · · · · · · · · · · · ·	Free	Free	10	521456E	2/86		
	01.00.020	not less than 5 litres		1100		0211002	-,00	••	
	84.36.009		Free	Free	10	521632L	2/86	• .•	
	0.1.00.000	Rotary bin condenser and raw stock lubricating system				,	-,		
	84.40.029	Transparent ironer hoods for industrial ironers	Free	Free	10	521537E	2/86		
	84.45.009	Gerro hydraulic two pillar motor press, capacity	Free	Free	10	503533D			
		3000 kN					•		
	84.45.009	Multiwork MW-35 hydraulic machine for bending, cutting,	Free	Free	10	503396K	2/86		
		notching and punching metal sections							
	84.45.009	• •	Free	Free	10	521608H	2/86		
	84.47.009	**	Free	Free	10	521454J	2/86		
	84.58.000		Free	Free	10	521503L	2/86		
		Automatic water closet	Free	Free	10	521470L	2/86		
	84.59.059	Air horns	Free	Free	10	504130K	2/86		
	84.59.059	Automatic clutch fluid filling machine	Free	Free	10	504227F	2/82		
		<del>-</del>	Free	Free	10	504061C	2/86	• •	
		Patient turnplate	Free	Free	99	521564B	2/86		
	84.59.059	Tyre vulcanisers	Free	Free	10	504224A	2/86	• •	
		Air manually operated solid forged or rolled	Free			501778F	10/85	• •	
		steel AISI 304 or AISI 316 3 way control valves							
	84.61.021	AIR RELIEF VALVES (FOR RELEASING AIR FROM WATER	Free			581514C	4/86	• •	
		SUPPLY SYSTEMS) VIZ;							
		Bronze, brass or gunmetal bodies - 32mm (11/4'')							
		and over;							
		Cast iron bodies - 175mm (7'') and over,							
		Cast steel and stainless steel - all sizes;							
		Automatic air eliminators — up to 15mm							
		ALUMINIUM BODIED SOLENOID VALVES, sizes 9.5mm and 12.7mm	Free		••	580044H	6/85		
	84.61.021	AUTOMATIC PROCESS CONTROL VALVES (OTHER THAN QUARTER	Free		••	581515A	4/86	• •	
		TURN; A VALVE CONTROLLED BY A CONTROLLING INSTRUMENT)							
		VIZ:							
		Diaphragm operated - all sizes							
		Electrically operated - all sizes							
		Hydraulically operated - all sizes							
		Stainless steel piston operated - all sizes							
		BALL VALVES OR SPHERICAL PLUG VALVES VIZ;	Free		•••	581517H	4/86	••	
		All ball valves 175mm (7'') and over							
		Trunnion mounted ball valves - all sizes							
		''V'' port ball valves - all sizes							
		Ball valves with three or more ports - all sizes							
		Ball valves with three or more ports - all sizes Metal seated ball valves - all sizes							