Tariff Industry Assistance (Decision) Notice No. 1986/16-continued

	Tariff Item	Description of Goods	Rates of Normal	Duty Pref.	Part II Ref.	Ref. No.	Effective From To	
	84.24.051 84.59.059 84.59.059 84.59.059	Carraro Air-Omega single seed drill Gaspardo pneumatic precision seed drill Precure tread finishing line Quilting frames Ratchet Safety Tensioner unit 50 mm belt width Check valves (valves which prevent reversal of flow) viz;	Free Free Free Free Free	Free Free Free Free	10 10 15 10 10	581633F 521229E 540723A 580978K 581626C 581519D	5/85 2/86 3/86 2/86 10/85 4/86	
		In line steel bodied check valves — over (3/4''), SWING, TILTING DISC AND DUAL PLATE: Brass, bronze or gunmetal bodies — 125 mm (5'') and above Cast steel bodied ANSI class 600 — sizes 400 mm (16'') and 500 mm (20'')						
		Iron or steel bodies 40 mm (11/2'') and below Iron or steel bodies - 900 mm (36'') and over Plastic bodied - all sizes excluding aerosol types Stainless steel bodied - 40 mm (11/2'') and below						
		Stainless steel bodied 500 mm (20'') and over Stainless steel bodied with flanged end connections - all sizes LIFT, GLOBE OR PISTON: (Non Hydraulic)						
		Aluminium bodied — all sizes Brass, bronze or gunmetal bodied — 200 mm (8'') and above Cast iron, steel and stainless steel bodied — all sizes						
		BALL CHECK: Cast iron, brass, bronze, gunmetal and plastic bodied (excluding aerosol types) — all sizes Steel and stainless steel bodied — 40 mm (11/2'')						
		and over Back flow preventors, reduced pressure principle FOOT VALVES: Cast iron, carbon steel or stainless steel bodied - 350 mm (14'') and over						
		Brass, bronze or gunmetal bodied - 65 mm (21/2'') and over UL (underwriters laboratory) approved valves for LPG service						
		Flush 77 ventiler (drinker) Globe valves, stop valves, piston valves, angle valves, radiator valves, and needle valves (valves which control the medium by the direct action of a disc against a seat) viz; Globe valves: Aluminium, plastic, steel and stainless steel bodied Brass, bronze or gunmetal bodied — 225 mm (9'')	Free Free			503171A 581522D	1/86 4/86	
		and over Cast iron bodied - up to 32mm (11/4'') Cast iron bodied - 175mm (7'') and over Cast iron bodied without copper alloyed internals						
		Dorot 04 series sizes 40 mm, 50 mm and 80 mm Dorot 05 series sizes 50 mm with 20 mm port Dorot 72 size 50 mm with 12 mm port leafield model A5, inflation, rapid deflation valves Nupro D4L and D4S series valves						
		Rinnai 3/8'' flame failure valve Needle valves: brass, bronze or gunmetal bodied - 20mm (3/4'') and above Stainless steel bodied - 19mm (3/4'')						
		and above Steel bodied - 19 mm (3/4'') and over Bellows sealed - all sizes with 3 or more parts - all sizes Radiator valves:						
		Double regulating, microbore, thermostatic or preset radiator valves - all sizes Isolating regulating valves - all sizes Other:						
	84.61.021	Piston valves Hopkinsons STS bronze bodied valves models; 8113, 8123, 8133, 8143 and 8173 Hydraulic valves viz; Flow control valves:	Free			581512G	4/86	
		Electrically modulated - all sizes Module or sandwich valves - all sizes Needle valves 50mm (2'') size and above Pressure and pressure/temperature compensated flow				·		
		valves — all sizes Flow dividers and flow divider/combiners — all sizes Flow control cartridges — all sizes Pressure control valves:						