## NEW ZEALAND GAZETTE

## Tariff Industry Assistance (Advertisement) Notice No. 1987/19-continued

ariff		Name and Address	Part II	Appn. Ref.	*Category of
tem	Description of Goods	of Applicant	Ref.	No.	Appn.
	motor coaches Split bolt, bolt on type overhead line tap				
	connectors suitable for tap connections on copper				
	lines, having overall diameters from 2.74mm to				
	14.76mm (0.108in. to 0.58in.) and split				
	bolt, bolt on type overhead line tap connectors				
	suitable for tap connections on aluminium lines				
	having overall diameters from 6.35mm to 14.61mm (0.250in. to 0.575in.)				
	Trailer plugs and sockets, viz;				
	4 pole, 5 pole and 7 pole				
	Wire and cable ring tongue connecting lugs,				
	crimp type, uninsulated, for conductors up to				
	185mm+ in cross-sectional area				
	EXCLUDING:				
	Compression type jointing sleeves, peculiar for use in jointing solid copper, stranded copper and				
	copper coated conductors, used in				
	telecommunication and power line wires and in				
	standard metric lugs				
	Wire connectors in strips				
5.19.052	REQUESTED APPROVAL		00	NO 0007145	
hole Item	Sockets, and plugs therefor, wire and cable connectors and the like		99	HO 682714E	VA
	EXCLUDING:				
	(1) Part II Duty Free concession already approved				
	under Tariff Item				
	(2) Aluminium compression fittings, peculiar for				
	use in jointing and terminating aluminium wire				
	and cable, excluding;				
	Fittings, when declared by a manufacturer for				
	use on; (a) Three core sector cable				
	(b) Four core sector cable exceeding 185mm+				
	cross-sectional area				
	(3) Battery isolaters, peculiar for use on all				
	types of storage batteries including				
	automotive and marine batteries				
	(4) Co-axial plugs, car-radio type				
	(5) Industrial and protected type plugs, sockets, cable couplers				
	(6) Appliance inlets and switch sockets,				
	rated 110 to 415 volts and up to 63 amps,				
	excluding;				
	Aluminium clad industrial plugs, sockets, cable				
	couplers appliances inlets and switch sockets, with maximum voltage rating of 500 V AC/DC, from				
	16-63 amps continuous rated current, flat				
	formation (i.e. round pins in a straight line)				
	pin/socket configuration				
	(7) Plugs, sockets, tap-ons, cord extension				
	sockets, 250 volts, 15 amp maximum rating				
	(8) Sockets and plugs therefor, wire and cable connectors and the like: excluding those of a				
	kind commonly used with:				
	(a) tractors for articulated vehicles, being				
	tractors that are designed for operation solely				
	or principally on the highway; or				
	(b) vehicles of 87.02 other than air-cushioned				
	vehicles or assembled convertible road/rail motor coaches				
	(9) Split bolt, bolt on type overhead line tap				
	connectors suitable for tap connections on copper				
	lines, having overall diameters from 2.74mm to				
	14.76mm (0.108in. to 0.58in.) and split				
	bolt, bolt on type overhead line tap connectors				
	suitable for tap connections on aluminium lines				
	having overall diameters from 6.35mm to 14.61mm (0.250in. to 0.575in.)				
	(10) Trailer plugs and sockets, viz;				
	4 pole, 5 pole and 7 pole				
	(11) Wire and cable ring tongue connecting lugs,				
	crimp type, uninsulated, for conductors up to				
	185mm+ in cross-sectional area, excluding;				
	Compression type jointing sleeves, peculiar for				
	use in jointing solid copper, stranded copper and copper coated conductors, used in				
	telecommunication and power line wires and in				
	standard metric lugs				· .
	(12) Wire connectors in strips				
.19.059	CURRENT APPROVAL			_	
	A.M.P. electrical terminals in strip and loose	Gartner Engineering Ltd	99	114027C	VA
	form	PO Box 13-441			
		Onehunga			