

## Tariff Industry Assistance (Decision) Notice No. 1988/26—continued

Tariff Item	Description of Goods	Rates of Duty		Part II Ref.	Ref. No.	Effective	
		Normal	Pref.			From	To
	BP10EV BR9ET BUHW B7EMV BCPR6EP-8 B4HV BR10ET BUHW-2 BP4EQ-13 BRE813L BCPR6EP-11 B6HV BR7EQ BUHW-1 BP5EQ-13 BZ9EV L8A B7HV BR8EQ BU8H BP6EQ-13 BUZHW B8EG B8HV BR7EQ-14 BU10H BP7EQ-13 BUZHW-2 B9EG B9HV BR8EQ-14 BP4HK BR8EV A9EFP B10EG B10HV BR9EQ-14 BP6HK BR9EV AU10EFP B11EG BP6HV BPR5EK-A BP8HK BR10EV B8EGP						
HO	8519.21.00) Record players	Free	Free	99	880002C	7/88	..
	8519.29.00) NOTE: This concession will also cover machines which incorporate an amplifier and transducer (loudspeaker), provided these are housed within the same cabinet as the player itself						
WN	8529.10.19 Directive phased array antenna	Free	Free	99	721583F	5/88	..
HO	8544.11.01 Copper winding wire insulated with lacquer or enamel under 0.125mm or over 1.60mm diameter	5	Free	99	780894B	5/88	..
WN	8708.29.01 One only soft top for 1980 Fiat convertible	Free	Free	99	721617D	5/88	..
WN	8708.91.19 Radiator pressure caps	Free	Free	99	721620D	5/88	..
AK	8714.20.00 Parts and accessories for ortho kinetic travel chairs	Free	Free	99	703225A	5/88	..
AK	Chapter 90 Electrical measuring, checking, analysing or automatically controlling instruments and apparatus; EXCLUDING: (1) Electric current controllers/indicators, up to 240v (2) Frequency meters, flush mounting pointer type with circular or quadrant scales, accuracy class of 0.5 and having face size of 72mm or 96mm square (3) Milk cryoscopes (4) Moving coil and moving coil/rectifier ammeters and voltmeters, including microammeters, milliameters and D.C. millivoltmeters for use with external shunts, flush mounting horizontal sector scales, accuracy class 2.5 and having body diameter of between 54 and 70mm (5) Moving coil and moving coil/rectifier ammeters and voltmeters, including milliameters and D.C. millivoltmeters, for use with external shunts, flush mounting with circular or quadrant scales accuracy class 1.5 and having face size of 72mm or 96mm square (6) Moving iron ammeters and voltmeters including milliameters, flush mounting and quadrant scales to accuracy class 1.5 and having face size of from 72mm to 144mm square inclusive (7) Temperature, pressure, humidity and moisture control and measuring devices (8) Industrial type batch and predetermining batch counters, but not including digital electronic frequencies above 1MHz (9) Variable speed controllers for A.C. motors, sizes up to and including 255 kw (10) Data logging systems designed for the measuring, indicating of physical data such as temperature, humidity, voltage, current, power and flow pressure EXCLUDING: Public water supply data logging equipment, (11) Echo-sounding, ultra-sonic and detecting equipment having a maximum depth range of up to 110m, excluding hermetically sealed units (12) Bin and hopper level control instruments and apparatus (13) Electronic differential thermostat switches designed to monitor or control the flow of gases, liquids or solids in the control of forced circulation solar heating systems, controlling loads up to 10hp or 7.5 kilowatts resistive (14) Electronic marine instruments for recording boat speed and distance other than Decca Logs and Seafarer Logs (15) Energy management systems, peculiar to use for measuring, analysing and controlling electrical demand (16) Gas detection systems, peculiar for use in commercial and/or industrial environments, which measure and report concentrations of flammable or toxic gases in the air via alarm and/or analogue (17) Moving iron ammeters and voltmeters, flush mounting, quadrant scale, to accuracy class 1.5 and having face sizes from 72mm to 144mm square (18) Moving coil and moving coil/rectifier ammeters and voltmeters, flush mounting, having face areas of between 5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales NOTE: circular, sector and quadrant type scales are illustrated in Fig. 2 on pages 11 and 12 of BS 3693, PART 1, 1964, 'The Design of Scales and Indexes.' (19) Portable electrically powered gas leak detector, gas detector and gas monitor and smoke warning alarms (20) Post payment self-service petrol dispensing systems (21) Power factor correction systems, including power factor controllers and ancillary equipment mounted in a common cubicle and designed to measure and automatically control the overall power factor in a 3-phase electrical installation, and such power factor controllers when imported separately	Free	Free	99	703218J	5/88	..