

Tariff Industry Assistance (Advertisement) Notice No. 1988/27—continued

Tariff Item	Description of Goods	Name and Address of Applicant	Part II Ref.	Appn. Ref. No.	*Category of Appn.
	(1) Better than 0.50% accuracy (2) Inconel metal Bourdon tubes (3) Monel metal Bourdon tubes (4) All stainless steel construction including case, Bourdon tube and movement, excluding those with a diameter of 100mm and 150mm (5) Rupture proof dial and blowout back (6) Horizontal diaphragm seal	PO Box 52163 Kingsland AUCKLAND			
9026.20.09	Glycerine filled pressure gauge, pressure 0-30,000 psi sizes: 38mm, 51mm, 63mm, 102mm, 153mm	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800119H	WA
9026.20.09	Glycerine filled pressure gauges up to 100 PSI	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800125B	WA
9026.20.09	Glycerine filled pressure gauges, peculiar for use in agricultural spray equipment e.g. reciprocating pumps used for spraying pesticide	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800133C	WA
9026.20.09	Mud pump pressure gauges	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800124D	WA
9026.20.09	Nuova Fima glycerine filled pressure gauges with dials from 63mm to 100mm for pressures ranging from 500 PSI to 8500 PSI or equivalent	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800123F	WA
9026.20.09	Pressure gauge 65mm diameter, all stainless steel, glycerine filled with pressure range up to 5000 PSIG	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800115E	WA
9026.20.09	Pressure gauges, 50mm (2'') diameter, when declared by a manufacturer for use by him, only in making or repairing pressure regulators used with industrial gases	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800116C	WA
9026.20.09	Pressure gauges having ultra high repeatability of 0.025% full scale, for monitoring industrial process pressures	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800117A	WA
9026.20.09	Pressure gauges, peculiar to use on homogenizers	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800118K	WA
9026.20.09	Wika glycerine filled pressure gauges, with dials from 63mm to 100mm, for pressures ranging from 500 PSI to or 8500 PSI equivalent	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800122H	WA
9026.80.09	Sigma thermocouple temperature controllers	Teltherm Instruments (NZ) Ltd PO Box 52163 Kingsland AUCKLAND	99	AK 800121K	WA
9026.90	CURRENT APPROVAL Pneumatic transmissions: (1) Force balance, blind transmitters, with pneumatic output of 19.6kPa to 112.9kPa (2.84 to 16.39lbs per sq.in.) Absolute pressure High range differential, pressure Gauge pressure Position Differential pressure, flow or liquid level Liquid level or density Repeater Vapour pressure Speed Sanitary liquid level Flow transmitters Consistency (2) Pneumatic receiver-controller only, with pneumatic input signals of 19.6kPa to 112.9kPa (2.84 to 16.39lbs per sq.in.) Pneumatic receiver indicating controllers Pneumatic receiver subpanels Pneumatic receiver control stations Pneumatic receiver controllers for automatic control stations Pneumatic receiver batch and multiple auto-selector control Pneumatic receiver single case cascade control systems Pneumatic receiver self-contained and gap action floating controllers Pneumatic receiver indicating/recording controllers Pneumatic receiver auto-selector control system Pneumatic receiver indicating recording control stations Pneumatic receiver ratio controllers Pneumatic receiver computer compatible control systems;		99	462163J	VA