

Tariff Industry Assistance (Decision) Notice No. 1988/29-continued

Tariff Item	Description of Goods	Rates of Duty		Part II Ref.	Ref. No.	Effective	
		Normal	Pref.			From	To
HO 8205.90.19 Whole item	Sets of two or more articles of Tariff Heading 82.05	Free	Free	99	780937K	7/88	..
HO 8206.00.00 Whole Item	Tools of two or more of the headings No's. 82.02 to 82.05, put up in sets for retail sale	Free	Free	99	780938H	7/88	..
HO 82.07	Interchangeable tools for hand tools, for machine tools or for power-operated hand tools (for example, for pressing, stamping, drilling, tapping, threading, boring, broaching, milling, cutting, turning, dressing, morticing or screw driving), including dies for wire drawing, extrusion dies for metal, and rock drilling bits: OTHER KINDS: EXCLUDING: (1) Drills (a) HSS and carbon/chrome/vanadium/tungsten steels, right hand helix;- (i) Straight shank Jobber length, double and single ended stub length and long series length 1mm to 13mm (1/16in. to 1/2in.) (ii) Straight shank long reach length 3mm to 13mm (1/8in. to 1/2in.) (iii) Reduce shank of any diameter including Blacksmith type 33/64in. to 1 1/4in. (iv) Reduced shank of any diameter (metal and wood-working) with standard or dowelling bit point 6mm to 13mm (1/4in. to 1/2in.) (v) Straight shank (4 flute core type) 3mm to 13mm (1/8in. to 1/2in.) (b) Tungsten carbide tipped twist from 2.381mm (c) Drill sets, containing above type drills in diameter ranges; Straight shank; 1mm to 13mm 1/16in. to 1/2in. Reduced shank; 6mm to 20mm 1/4in. to 3/4in. (d) Tungsten carbide tipped masonry, drills straight also reduced shank of any shank diameter 'short' or 'long' overall lengths within diameter range; 3mm to 32mm; 1/8in. to 1 1/4in. (e) Countersinks, single flute; 1/2in. shank 15.5mm to 19.5mm (f) Reamers, Parallel Machine, Tungsten Carbide tipped, non-adjustable; straight shank, all sizes under 14.29mm morse taper shank, all sizes over 14.29mm (g) Router bits, with cutting or working faces of high speed steel or of tungsten carbide (h) Milling Cutters; Tungsten Carbide tipped, circular other than throw away tip type (i) Facing Cutters, Tungsten Carbide tipped, circular other than throw away tip type (j) Profile and Cutter Heads, Tungsten Carbide and HSS Tipped for use with woodworking machines (k) Tool bits (pieces) high speed steel; Square 3mm to 16mm, all lengths Round 3mm to 13mm, all lengths Bevel 13mm to 26mm, all lengths Rectangular 4 x 10mm to 12 x 20mm, all lengths (2) Lathe tools (brazed on tips), Tungsten Carbide Tipped, standard pattern (3) Knives-tungsten carbide tipped-steel (4) Bits and reamers, rotary diamond (5) Bits and reamers, rotary, tungsten carbide, excluding; percussion, carbide insert and button types (6) Tools for pressing and stamping	Free	Free	99	880018K	7/88	..
AK 8409.91.01	Internal combustion engine parts viz:- cylinder sleeves	Free	Free	99	703398C	8/88	..
HO 8413.19.00	Metripumps	Free	Free	99	780940K	7/88	..
WN 8413.60.09	Varisco rotary gear pumps, with delivery outlets in excess of 76mm diameter and/or with a head greater than 70mm	Free	Free	99	721678F	5/88	..
AK 8414.59.09	Rotary positive displacement blower. Maximum pressure 15 PSI maximum vacuum 15" HG	Free	Free	99	703400J	7/88	..
AK 8421.39.09	High pressure air separators and filter purifiers with a minimum pressure rating of 27,500 KPA	Free	Free	99	703401G	6/88	..
WN 8431.31.09	Component parts of work platforms EXCLUDING: (1) Parts of general use (2) Stabiliser cylinders (3) Workman basket (4) Base assembly (5) Boom cylinders (6) Column assembly (7) Inner boom assembly	Free	Free	99	721764B	6/88	..