

Tariff Industry Assistance (Advertisement) Notice No. 1988/29—continued

Tariff Item	Description of Goods	Name and Address of Applicant	Part II Ref.	Appn. Ref. No.	*Category of Appn.
	<p>EXCLUDING:</p> <p>(a) Bulldozer blades, buckets and the like and their activating equipment, eg., hydraulic rams, trunnions, cylinder bracket assemblies and push arms</p> <p>(b) Wheeled front end loaders, (excluding track types) whether or not assembled, as defined by SAE Standard SAE J1057 (published in the Society of Automotive Engineers, Inc Handbook) which cannot rotate through the horizontal plane without movement of the wheels with a static tipping load in full turn capacity up to and including 16,000 kg as measured to SAE Standard J732c. This measurement shall be applied to these loaders equipped to the manufacturers' worldwide official specifications excluding tyre ballast and optional counterweights</p> <p>(c) Backhoe loaders, whether or not assembled, consisting of a tractor base or wheel loader base, two wheel drive, four wheel drive or crawler type, front or rear wheel steer, pivot steer or skid steer complete with backhoe (digger) mounted in any position whether capable of side shift or not, with king post, swing mechanism, with or without bucket, boom arm assembly (boom linkage) and Hydraulic cylinders having a boom swing travel of less than 360 degrees (commonly referred to as a TLB Tractor Loader Backhoe or Backhoe Loader)</p> <p>(d) Tractor mounted backhoe (diggers) and skid steer base mounted backhoe whether or not assembled, two or four wheel drive, front or rear steer, pivot steer or skid steer complete with backhoe (digger) mounted in any position whether capable of side shift or not, with king post, swing mechanism having a boom swing travel of less than 360 degrees</p> <p>(e) Four wheel drive, skid steer front end loaders (commonly known as Bobcat Loaders)</p> <p>(f) Rubber tracted loader with a lifting capacity up to 1000 kg</p>				
84.29)	Excavating machinery, other than machinery of a kind designed for mounting on tractors or other vehicles	Comptroller of Customs PO Box 2218 WELLINGTON	99	HO 880016C	A
84.31)	<p>EXCLUDING:</p> <p>(a) Bulldozer blades, buckets and the like and their activating equipment, eg., hydraulic rams, trunnions, cylinder bracket assemblies and push arms</p> <p>(b) Wheeled front end loaders, (excluding track types) whether or not assembled, as defined by SAE Standard SAE J1057 (published in the Society of Automotive Engineers, Inc Handbook) which cannot rotate through the horizontal plane without movement of the wheels with a static tipping load in full turn capacity up to and including 12,995 kg as measured to SAE Standard J732c. This measurement shall be applied to these loaders equipped to the manufacturers' worldwide official specifications excluding tyre ballast and optional counterweights</p> <p>(c) Backhoe loaders, whether or not assembled, consisting of a tractor base or wheel loader base, two wheel drive, four wheel drive or crawler type, front or rear wheel steer, pivot steer or skid steer complete with backhoe (digger) mounted in any position whether capable of side shift or not, with king post, swing mechanism, with or without bucket, boom arm assembly (boom linkage) and Hydraulic cylinders having a boom swing travel of less than 360 degrees (commonly referred to as a TLB Tractor Loader Backhoe or Backhoe Loader)</p> <p>(d) Tractor mounted backhoe (diggers) and skid steer base mounted backhoe whether or not assembled, two or four wheel drive, front or rear steer, pivot steer or skid steer complete with backhoe (digger) mounted in any position whether capable of side shift or not, with king post, swing mechanism having a boom swing travel of less than 360 degrees</p> <p>(e) Four wheel drive, skid steer front end loaders (commonly known as Bobcat Loaders)</p> <p>(f) Rubber tracted loader with a lifting capacity up to 1000 kg</p>				
8429.51.00)	Self-propelled excavators	Comptroller of Customs PO Box 2218 WELLINGTON	99	701129G	WA
8429.52.00)	EXCLUDING:				
8429.59.00)	<p>(a) Wheeled front end loaders, (excluding track types) whether or not assembled, as defined by SAE Standard SAE J1057 (published in the Society of Automotive Engineers, Inc Handbook) which cannot rotate through the horizontal plane without movement of the wheels with a static tipping load in full turn capacity up to and including 16,000 kg as measured to SAE Standard J732c. This measurement shall be applied to these loaders equipped to the manufacturers' worldwide official specifications excluding tyre ballast</p>				