4106

NEW ZEALAND GAZETTE

Tariff Industry Assistance (Decision) Notice No. 1988/39-continued

Tariff Item	Description of Goods	Rates of Normal	Duty Pref.	Part II Ref.	Ref. No.	Effect From	ive To
	or quadrant scales, accuracy class of 0.5 and having face size						
	of 72mm or 96mm square (3) Milk cryoscopes						
	(4) Moving coil and moving coil/rectifier ammeters and						
	voltmeters, including microammeters, milliameters and D.C.						
	millivoltmeters for use with external shunts, flush mounting horizontal sector scales, accuracy class 2.5 and having body						
	diameter of between 54 and 70mm						
	(5) Moving coil and moving coil/rectifier ammeters and						
	voltmeters, including milliameters and D.C. millivoltmeters, for use with external shunts, flush mounting with circular or						
	quadrant scales accuracy class 1.5 and having face size of						
	72mm or 96mm square						
	(6) Moving iron ammeters and voltmeters including milliameters, flush mounting and quadrant scales to accuracy class 1.5 and						
	having face size of from 72mm to 144mm square inclusive						
	(7) Temperature, pressure, humidity and moisture control and						
	measuring devices (8) Industrial type batch and predetermining batch counters,						
	but not including digital electronic frequencies above lMHz						
	(9) Variable speed controllers for A.C. motors, sizes up to and						
	including 255 kw (10) Data logging systems designed for the measuring, indicating						
	of physical data such as temperature, humidity, voltage, current,						
	power and flow pressure						
	EXCLUDING: Public water supply data logging equipment,						
	(11) Echo-sounding, ultra-sonic and detecting equipment						
	having a maximum depth range of up to 110m, excluding						
	hermetically sealed units (12) Bin and hopper level control instruments and apparatus						
	(13) Electronic differential thermostat switches designed to						
	monitor or control the flow of gases, liquids or solids in						
	the control of forced circulation solar heating systems, controlling loads up to 10hp or 7.5 kilowatts resistive						
	(14) Electronic marine instruments for recording boat speed						
	and distance other than Decca Logs and Seafarer Logs						
	(15) Energy management systems, peculiar to use for measuring, analysing and controlling electrical demand						
	(16) Gas detection systems, peculiar for use in commercial						
	and/or industrial environments, which measure and report						
	concentrations of flammable or toxic gases in the air via alarm and/or analogue						
	(17) Moving iron ammeters and voltmeters. flush mounting,			÷			
	quadrant scale, to accuracy class 1.5 and having face sizes						
	from 72mm to 144mm square (18) Moving coil and moving coil/rectifier ammeters and						
	voltmeters, flush mounting, having face areas of between						
	5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales						
	NOTE: circular, sector and quadrant type scales are illustrated						
	in Fig. 2 on pages 11 and 12 of BS 3693, PART 1, 1964, "The						
	Design of Scales and Indexes.'' (19) Portable electrically powered gas leak detector, gas						
	detector and gas monitor and smoke warning alarms						
	(20) Post payment self-service petrol dispensing systems						
	(21) Power factor correction systems, including power factor controllers and ancillary equipment mounted in a common						
	cubicle and designed to measure and automatically control						
	the overall power factor in a 3-phase electrical						
	installation, and such power factor controllers when imported separately						
	(22) Telemetry system designed for the remote control						
	measuring and indicating of physical and electrical data,						
	such as voltage, current, power and position status (23) Electronic taximeters						
	(24) Ripple signal control equipment						
	(25) Parts of electrical weight or load measuring equipment; viz:						
	load cells, load bars, weigh cells, load transducers, weight transducers, strain gauge transducers, force transducers						
	Other than:						
	Hermetically sealed transducers (being gas tight), shock proof						
	transducers (being without fittings or attachments), explosion proof transducers, load pins, shackle pins, cannister						
	cells, single point cells, pancake cells, dual cantilever,						
0014 00 00	straight types Each counder with liquid crustal display and having bottom	Free	Free	00	8010720	3/00	
9014.80.00	Echo sounder with liquid crystal display and having bottom profile and digital readout	Free	Free	99	801072C	3/88	••
9014.80.00	Electronic marine instruments for recording boatspeed and	Free	Free	99	801073A	1/88	
	distance, as may be approved:						
	APPROVED: Decca logs, Seafarer logs, Furuno and Morioka models						
9026.80.09	Heimer thermostatic valve heads	Free	Free	99	800587H	8/88	••
9209.94.09	Parts and accessories for the musical instruments of	Free	Free	99	800551G	8/88	