

Tariff Industry Assistance (Decision) Notice No. 1988/39—continued

Tariff Item	Description of Goods	Rates of Duty		Part II Ref.	Ref. No.	Effective	
		Normal	Pref.			From	To
	Finnell Metal Productions Ltd Fisher and Paykel Kent Heating Kingsway Lock Out Aluminium T R Hillson Ltd						
AK 7217.11.00)	Uncoated roping wire - 0.19mm to 4.20m diameter	5	AU Free	99	800635A	7/88	..
7217.21.00)	1370 to 2050 N/mm ²						
7217.31.00)							
AK 7306.30.19)	Rectangular hollow sections of approved sizes	5	AU Free	99			
7306.60.00)	APPROVED SIZES: Rectangular hollow sections, sizes exceeding 127mm x 51mm Square hollow sections, sizes exceeding 89mm x 89mm		LDC Free		202533H	1/88	
					202534F	1/88	
AK 7317.00.09	Electro galvanised wire nails, ring shank counter sunk flat head diamond point SWG14 x SWG8 x 5/8''	Free	Free	99	800574F	8/88	..
AK 7326.90.09	Motor vehicle immobilizing wheel clamp devices	Free	Free	99	800599A	8/88	..
AK 7326.90.09	Processing lens annealed woven steel wire pads	Free	Free	99	800580L	8/88	..
AK 7326.90.09	Steel and tin plate culots (cup shaped gasket inserts)	Free	Free	99	800547J	8/88	..
AK 7606.12.09	External corner support tape consisting of a paper backing strip adhered to two uncoated aluminium strips	Free	Free	99	800559B	8/88	..
AK 7616.90.29	Intumescent fire and smoke seals	Free	Free	99	800581J	8/88	..
AK 8408.10.09	Watercooled engines, as may be approved; APPROVED: An engine for which the original engine manufacturer obtains a certificate certifying it as complying with a national Standard Specification, internationally acceptable, and attaining its maximum continuous shaft kilowatt rating under either DIN6270 (rating A) or BS 649; 1958 or SAE J816a, at an engine speed not exceeding 2000 rpm. An engine for which the original engine manufacturer obtains a certificate certifying it as complying with a national Standard Specification, internationally acceptable and attaining its maximum continuous shaft kilowatt rating at an engine speed exceeding 2000 rpm under DIN 6270 (rating A) or BS 649; 1958 or SAE J816a, provided that the maximum continuous shaft kilowatt rating is greater than 149 shaft kilowatts (200 shaft horsepower) Bukh diesel models; DV 30ME DV 36SME Caterpillar; 3208 D399 3306 marine propulsion 3406 marine propulsion 3408 marine propulsion 3412 marine propulsion D379 marine propulsion D398 marine engine D353 marine engine Chrysler models; 180 130 195 240 250 265 330 C.M.C. models; 4135 CaB-3, 6135 CaB-3, 12V135 CaB-3 Crusader models; CS-220 CS-270 CS-300 CH-270 CH-350 Cummins marine diesel engines: N-855-M NT-855-M1 V-504-M, V-555-M VT-903-M V-903-M VT-903-M1 VTA-903-M VT-1710-M VTA-1710-M1 VTA-1710-M2 KT-1150-M KTA-1150-M KT-2300-M KTA-2300-M Detroit diesel models; 6V-53 6-71 6V-71 6V-92	Free	Free	99	800575D	8/88	..