## CUSTOMS EDITION

## Tariff Industry Assistance (Advertisement) Notice No. 1988/45-continued

		of Applicant	Ref.	No.	Appn.
	designed for mounting on tractors or other vehicles	Private Bag			
+	EXCLUDING: (a) Bulldozer blades, buckets that have a S.A.E. rated	WELLINGTON			
+	capacity below 1.53m3 and the like and their activating				
	equipment, eg., hydraulic rams, trunnions, cylinder				
	bracket assemblies and push arms (b) Wheeled front end loaders, (excluding track types)				
	whether or not assembled, as defined by SAE				
	Standard SAE J1057 (published in the Society of				
	Automotive Engineers, Inc Handbook) which cannot rotate through the horizontal plane without movement of the				
	wheels with a static tipping load in full turn capacity				
	up to and including 12,000 kg as measured to SAE Standard				
	J732c. This measurement shall be applied to these loaders equipped to the manufacturers' worldwide official				
	specifications excluding tyre ballast and optional				
	counterweights				
	(c) Backhoe loaders, whether or not assembled, consisting of a tractor base or wheel loader base, two wheel drive,				
	four wheel drive or crawler type, front or rear wheel				
	steer, pivot steer or skid steer complete with backhoe				
	(digger) mounted in any position whether capable of side shift or not, with king post, swing mechanism, with or				
	without bucket, boom arm assembly (boom linkage) and				
	hydraulic cylinders having a boom swing travel of less				
	than 360 degrees (commonly referred to as a TLB Tractor Loader Backhoe or Backhoe Loader)				
)	(d) Tractor mounted backhoe (diggers) and skid steer base				
	mounted backhoe whether or not assembled, two or four				
	wheel drive, front or rear steer, pivot steer or skid steer complete with backhoe (digger) mounted in any				
	position whether capable of side shift or not, with king				
	post, swing mechanism having a boom swing travel of less				
	than 360 degrees				
	(e) Four wheel drive, skid steer front end loaders (commonly known as Bobcat Loaders)				
	(f) Rubber tracted loader with a lifting capacity up to				
	1000 kg		~~	<b>UO</b> 000418	
84.65	Machine-tools for working wood, cork, bone, ebonite (vulcanite), hard artificial plastic materials or	Comptroller of Customs PO Box 2218	99	HO 800413	H WA
	other hard carving materials, other than machines falling	WELLINGTON			
	within heading No. 84.67:				
	EXCLUDING: Edgebanding machines which perform the following functions				
	only viz: - the application of preglued edging tape coils				
	of PVC, melamine or wood veneer to hand fed panels by means				
	of glue reactivation, with or without a tape front and/or end cut off function				
	(Edgebanding machines which have additional functions				
	to those specified above will qualify for this concession provided the additional functions are relevant to				
	edgebanding machines and are catalogued as being for the				
	edgebanders concerned)				
	Drill presses, bench or floor mounting column type, not exceeding capacities in mild steel up to and including				
	42mm. (Multi-purpose or composite machines incorporating				
	this function fall within this exclusion)				
	Samco model LP15 vertical and bobbin sander Surface planers, buzzers or jointers with blade not				
	exceeding 310mm				
	Thicknessers, with a capacity up to and including 330mm.				
	(Multi-purpose or composite machines incorporating this function fall within this exclusion)				
	Woodturning lathes, for operation with tools held by the				
	hand or semi-automatic (but not including fully automatic)				
	End-matching machines Woodworking machinery; viz:				
	Automatic firewood saws				
	Bandsaws with throat capacity not exceeding 535mm (21in.)				
	Box nailing machines Breast benches				
	Circular breakdown saws				
	Circular saw benches, hand-feed, including builders'				
	treadle saw benches, with blade diameter not exceeding 360mm				
	Cut-off saws, pendulum type with motor not exceeding				
	3.75 kW (5 h.p.) and with blade diameter not exceeding				
	500mm (20in.) Docking saws				
	Dovetailing machines with single spindle and manual feed				
	Drill presses, wall mounting, radial type not exceeding				
	22.2mm capacity in mild steel Horizontal dowel boring machines, not exceeding 25mm				
	capacity in mild steel				
	Log cut-off swing saws				