

## Tariff Industry Assistance (Decision) Notice No. 1988/46-continued

Tariff Item	Description of Goods	Rates of Duty		Part II Ref.	Ref. No.	Effective	
		Normal	Pref.			From	To
AK 76.06	Aluminium sheet having a permanent PVC vinyl or plastic lamination	Free	Free	99	801270K	10/88	..
AK 7606.12.09	Aluminium alloy sheet and coil continuously anodised, as may be approved: APPROVED: ALANOD ANO-COIL	Free	Free	99	801287D	10/88	..
AK 7606.12.09	Aluminium alloy sheet and plate - alloy 6082, T6	Free	Free	99	801274B	10/88	..
AK 7607.20.00	Aluminium foil, '0' temper, bright finish up to and including 0.150mm thickness, bonded to low density polyethylene or copolymer 0.040mm to 0.050mm thickness	Free	Free	99	801648J	11/88	..
AK 82.07	Interchangeable tools for hand tools, for machine tools or for power-operated hand tools (for example, for pressing, stamping, drilling, tapping, threading, boring, broaching, milling, cutting, turning, dressing, morticing or screw driving), including dies for wire drawing, extrusion dies for metal, and rock drilling bits: OTHER KINDS: EXCLUDING: (1) Drills (a) HSS and carbon/chrome/vanadium/tungsten steels, right hand helix;- (i) Straight shank Jobber length, double and single ended stub length and long series length 1mm to 13mm (1/16in. to 1/2in.) (ii) Straight shank long reach length 3mm to 13mm (1/8in. to 1/2in.) (iii) Reduce shank of any diameter including Blacksmith type 33/64in. to 1 1/4in. (iv) Reduced shank of any diameter (metal and wood-working) with standard or dowelling bit point 6mm to 13mm (1/4in. to 1/2in.) (v) Straight shank (4 flute core type) 3mm to 13mm (1/8in. to 1/2in.) (b) Tungsten carbide tipped twist from 2.381mm (c) Drill sets, containing above type drills in diameter ranges; Straight shank; 1mm to 13mm 1/16in. to 1/2in. Reduced shank; 6mm to 20mm 1/4in. to 3/4in. (d) Tungsten carbide tipped masonry, drills straight also reduced shank of any shank diameter 'short' or 'long' overall lengths within diameter range; 3mm to 32mm; 1/8in. to 1 1/4in. (e) Countersinks, single flute; 1/2in. shank 15.5mm to 19.5mm (f) Reamers, parallel machine, tungsten carbide tipped, non-adjustable; straight shank, all sizes under 14.29mm morse taper shank, all sizes over 14.29mm (g) Router bits, with cutting or working faces of high speed steel or of tungsten carbide (h) Milling cutters; tungsten carbide tipped, circular other than throw away tip type (i) Facing cutters, tungsten carbide tipped, circular other than throw away tip type (j) Profile and cutter heads, tungsten carbide and HSS tipped for use with woodworking machines (k) Tool bits (i) M42 Cobalt High Speed Steel Imperial sizes 1/2 x 3/32 x 4 1/2'' Bevel 5/8 x 3/32 x 5'' Bevel 3/4 x 1/8 x 6'' Bevel 7/8 x 1/8 x 7'' Bevel 1 x 3/16 x 8'' Bevel 3/16 x 2 1/2'' Square 3/16 x 3'' Square 1/4 x 2 1/2'' Square 1/4 x 3'' Square 1/4 x 4'' Square 5/16 x 2 1/2'' Square 5/16 x 3'' Square 5/16 x 4'' Square 3/8 x 3'' Square 3/8 x 4'' Square 3/8 x 6'' Square 1/2 x 4'' Square 1/2 x 6'' Square 5/8 x 4 1/2'' Square 3/4 x 5'' Square 1 x 7'' Square (ii) M2 High Speed Steel Imperial Sizes	Free	Free	99	800284D	5/88	..