

## Tariff Industry Assistance (Decision) Notice No. 1988/13-continued

Tariff Item	Description of Goods	Rates of Duty		Part II Ref.	Ref. No.	Effective	
		Normal	Pref.			From	To
AK 82.07	<p>Simonds furn-wood Simonds si-ply Interchangeable tools for hand tools, for machine tools or for power-operated hand tools (for example, for pressing, stamping, drilling, tapping, threading, boring, broaching, milling, cutting, turning, dressing, morticing or screw driving), including dies for wire drawing, extrusion dies for metal, and rock drilling bits: OTHER KINDS: EXCLUDING: (1) Drills (a) HSS and carbon/chrome/vanadium/tungsten steels, right hand helix:- (i) Straight shank Jobber length, double and single ended stub length and long series length 1mm to 13mm (1/16in. to 1/2in.) (ii) Straight shank long reach length 3mm to 13mm (1/8in. to 1/2in.) (iii) Reduce shank of any diameter including Blacksmith type 33/64in. to 1 1/4in. (iv) Reduced shank of any diameter (metal and wood-working) with standard or dowelling bit point 6mm to 13mm (1/4in. to 1/2in.) (v) Straight shank (4 flute core type) 3mm to 13mm (1/8in. to 1/2in.) (b) Tungsten carbide tipped twist from 2.381mm (c) Drill sets, containing above type drills in diameter ranges: Straight shank; 1mm to 13mm 1/16in. to 1/2in. Reduced shank; 6mm to 20mm 1/4in. to 3/4in. (d) Tungsten carbide tipped masonry, drills straight also reduced shank of any shank diameter "short" or "long" overall lengths within diameter range; 3mm to 32mm; 1/8in. to 1 1/4in. (e) Countersinks, single flute; 1/2in. shank 15.5mm to 19.5mm (f) Reamers, Parallel Machine, Tungsten Carbide tipped, non-adjustable; straight shank, all sizes under 14.29mm morse taper shank, all sizes over 14.29mm (g) Router bits, with cutting or working faces of high speed steel or of tungsten carbide (h) Milling Cutters; Tungsten Carbide tipped, circular other than throw away tip type (i) Facing Cutters, Tungsten Carbide tipped, circular other than throw away tip type (j) Profile and Cutter Heads, Tungsten Carbide and HSS Tipped for use with woodworking machines (k) Tool bits (pieces) high speed steel; Square 3mm to 16mm, all lengths Round 3mm to 13mm, all lengths Bevel 13mm to 26mm, all lengths Rectangular 4 x 10mm to 12 x 20mm, all lengths (2) Lathe tools (brazed on tips), Tungsten Carbide Tipped, standard pattern (3) Knives-tungsten carbide tipped-steel (4) Bits and reamers, rotary diamond (5) Bits and reamers, rotary, tungsten carbide, excluding: percussion, carbide insert and button types</p>	Free	Free	99	702229J	2/88	..
WN 8302.42.00 (83.02.015)	Pivot sliding door set comprising one pair of plastic U-tracks, 2 lower steel pivots and 2 upper steel pivots, adjustable in sleeves	Free	Free	99	720739F	11/87	..
DN 8402.99.00	Segmental saws and teeth of tungsten carbide 30'' and over	Free	Free	99	660537A	2/88	..
HO 8413.60.09	Hydrochloric acid centrifugal process pumps and hydrochloric acid rotary positive displacement pumps	Free	Free	99	780820J	2/88	12/88
CH 8413.70.09	Grundfos vertical and horizontal multistage centrifugal pumps excluding all motors except single phase motors, as may be approved: APPROVED: CR2, CR4, CR8, CR16, CR30, CR60, CH2-30, CH2-50, CH4-20, CH4-30 and CH4-40	Free	Free	99	740478G	3/88	..
AK 8413.70.09	Suction boxes for 1 megawatt 10 stage non positive displacement centrifugal pump - 10 impeller	Free	Free	99	702238H	2/88	..
HO 8414.10.09	Hydrochloric acid resistant blowers for temperatures to 130°C	Free	Free	99	780755E	2/88	12/88
HO 8419.39.00	Dryers/calciners for handling wet hydrochloric acid hydrate cake	Free	Free	99	780746F	2/88	12/88
HO 8419.39.00	HCl regeneration plant	Free	Free	99	780745H	2/88	12/88
HO 8419.40.00	Hydrochloric acid resistant process reaction vessels for temperatures to 130°C	Free	Free	99	780747D	2/88	12/88
HO 8419.40.00	Hydrochloric acid stream absorbers/scrubber/reactors for	Free	Free	99	780749L	2/88	12/88