Tariff	Description of Coods	Name and Address	Part II	Appn. Ref.	*Category of
Item	Description of Goods	of Applicant	Ref.	No.	Appn.
8544.11.01	Copper winding wire insulated with laquer or enamel under $0.160\mathrm{mm}$ and over $1.60\mathrm{mm}$ diameter	WELLINGTON Coils Specialists NZ Ltd PO Box 2365	99	7808941	3 A
8704.10.00	$\mbox{TWA52LDN}$ series Nissan diesel dump truck complete with $8\mbox{m}^3$ U section dump body	TAURANGA Nissan New Zealand Ltd PO Box 61133 Otara	99	AK 7031860	G A
8714.20.00	Parts and accessories for ortho kinetic travel chairs	AUCKLAND Group Pharmaceuticals Ltd C/-G.N. Bowerman, Tariff Consultant Colebrook Bros Ltd PO Box 1296 AUCKLAND	99	AK 703225/	A A
Chapter 90	CURRENT APPROVAL				
	Electrical measuring, checking, analysing or automatically controlling instruments and apparatus; EXCLUDING:		99	740496I	: VA
	(1) Electric current controllers/indicators, up to 240v (2) Frequency meters, flush mounting pointer type with circular or quadrant scales, accuracy class of 0.5 and				
	having face size of 72mm or 96mm square (3) Milk cryoscopes				
	(4) Moving coil and moving coil/rectifier ammeters and voltmeters, including microammeters, milliameters and D.C. millivoltmeters for use with external shunts, flush				
	mounting horizontal sector scales, accuracy class 2.5 and having body diameter of between 54 and 70mm (5) Moving coil and moving coil/rectifier ammeters and				
	voltmeters, including milliameters and D.C. millivoltmeters, for use with external shunts, flush mounting with circular or quadrant scales accuracy class				
	1.5 and having face size of 72mm or 96mm square (6) Moving iron ammeters and voltmeters including				
	milliameters, flush mounting and quadrant scales to accuracy class 1.5 and having face size of from 72mm to 144mm square inclusive				
	(7) Temperature, pressure, humidity and moisture control and measuring devices				
	(8) Industrial type batch and predetermining batch counters, but not including digital electronic frequencies above lMHz				
	(9) Variable speed controllers for A.C. motors, sizes up to and including 255 kw(10) Data logging systems designed for the measuring,				
	indicating of physical data such as temperature, humidity, voltage, current, power and flow pressure EXCLUDING:				
	Public water supply data logging equipment,				
	(11) Echo-sounding, ultra-sonic and detecting equipment having a maximum depth range of up to 110m, excluding hermetically sealed units				
	(12) Bin and hopper level control instruments and apparatus (13) Electronic differential thermostat switches designed				
	to monitor or control the flow of gases, liquids or solids in the control of forced circulation solar heating systems, controlling loads up to 10hp or 7.5 kilowatts resistive				
	(14) Electronic marine instruments for recording boat speed and distance other than Decca Logs and Seafarer Logs (15) Energy management systems, peculiar to use for				
	measuring, analysing and controlling electrical demand (16) Gas detection systems, peculiar to use in commercial				
	and/or industrial environments, which measure and report concentrations of flamable or toxic gases in the air via alarm and/or analogue				
	(17) Moving iron ammeters and voltmeters, flush mounting, quadrant scale, to accuracy class 1.5 and having face sizes from 72mm to 144mm square				
	(18) Moving coil and moving coil/rectifier ammeters and voltmeters, flush mounting, having face areas of between				
	5184 square millimeters and 9216 square millimeters and having sector, quadrant or circular scales NOTE: circular, sector and quadrant type scales are				
	illustrated in Fig. 2 on pages 11 and 12 of BS 3693, PART 1, 1964, 'The Design of Scales and Indexes.' (19) Portable electrically powered gas leak detector, gas				
	detector and gas monitor and smoke warning alarms (20) Post payment self-service petrol dispensing systems			•	
	(21) Power factor correction systems, including power factor controllers and ancillary equipment mounted in a common cubicle and designed to measure and automatically				
	control the overall power factor in a 3-phase electrical installation, and such power factor controllers when imported separately				
	(22) Telemetry system designed for the remote control measuring and indicating of physical and electrical data,	-			