[Note: The unwanted emission limits applicable to frequencies within each specified range shall be determined in accordance with the following formula:

$$y = mx + C$$

where - $y = dBW$, $\quad x = MHz$, $\quad m = \dfrac{dy}{dx}$,

$C =$ the value of y where $x = 0$ (the y intercept)]

(f) Class of emissions permitted under this licence:

256KF8EHF

(g) Horizontal radiation pattern of transmitter: [maximum e.i.r.p. (in dBW) per sector (in degrees relative to True North)]

29.0 dBW	$150^\circ - 240^\circ$
23.0 dBW	$240^\circ - TN - 5^\circ$
9.0 dBW	5°
23.0 dBW	$5^\circ - 150^\circ$

(h) Antenna polarisation of transmitter: SLANT

(i) Antenna height: 10 metres above ground level

2.   Other particulars.

(a) Receive coverage locations:

Map	Grid References
NZMS 262-13	424713, 449742, 489779

(b) Maximum permitted interfering signals applying to receive coverage locations (measured at a height of 10 metres above ground level):

Co-channel:	21 dBμV/m.
Adjacent channel (+/- 100kHz):	31 dBμV/m.
Adjacent channel (+/- 200kHz):	58 dBμV/m.

(c) Commencement date of licence: 1 November 1990.

(d) Expiry date of licence: 31 October 2010.