

(g) Horizontal radiation pattern of transmitter:
 [maximum e.i.r.p. (in dBW) per sector (in degrees
 relative to True North)]

000 degrees up to 076 degrees: 10 dBW.
 Over 076 degrees up to 084 degrees: 9.1 dBW.
 Over 084 degrees up to 360 degrees: 10 dBW.

(h) Antenna polarisation of transmitter: Vertical

(i) Antenna height: 20 metres above ground level

2. Other particulars.

(a) Receive coverage locations:

<u>Map</u>	<u>Grid References</u>
NZMS 260-Q07	303075

(b) Maximum permitted interfering signals applying to
 receive coverage locations: 45 dB μ V/m.

(c) Commencement date of licence: 29 June 1990

(d) Expiry date of licence: 28 June 2010

(e) Conditions applying to the exercise of the
 rightholder's rights under this licence:

The rightholder shall not transfer the rightholder's interest in this licence to any foreign government, or to any party on behalf of any foreign government, without first obtaining the written approval of the Secretary of Commerce.

The maximum permitted interfering signals above shall be measured at a height of 10 metres above ground level.

The maximum interfering signal shall be 45 dB μ V/m measured with a vertically polarised antenna or 25 dB μ V/m measured with a horizontally polarized antenna.