

Tariff Industry Assistance (Advertisement) Notice No. 1991/15-continued

Tariff Item	Description of Goods	Name and Address of Applicant	Part II Ref.	Appn. Ref. No.	*Category of Appn.
6305.31.09	Knitted polyethylene rachel knitted bags	Burlington Customs Brokerage PO Box 1296 AUCKLAND	99	TCU 984053C	A
6403.19.11)	CURRENT APPROVAL				
6403.99.19)	Cycle racing footwear		99	703359B	VA
64.02)	REQUESTED APPROVAL				
64.03)	Cycle racing footwear	Ninness Sports Ltd C/- PO Box 3230 AUCKLAND	99	TCU 985392J	VA
64.04)					
6404.19.19	Mukluks (polar boots) - Asics type F-DX	DSIR Antarctic Division C/- Pengelly's PO Box 14621 Kilbirnie WELLINGTON	99	TCU 982728F	A
7117.19.00)	CURRENT APPROVAL				
7117.90.19)	Jewellers findings		99	680050F	VA
Section VII)	REQUESTED APPROVAL				
Section XIV)	Jewellers findings	Prints & Imports Ltd C/- Prestige Customs Services Ltd PO Box 35-439 Browns Bay AUCKLAND	99	TCU 984658B	VA
Section XV	CURRENT APPROVAL Plugs, clips and similar fittings peculiar to use by builders for fixing articles to concrete or plaster EXCLUDING: Drop in Masonry Flush Anchors made from stainless or mild steel with internal thread diameter from 6.00mm to 20mm Concrete Inserts stainless or mild steel with internal thread diameter 6.00mm to 24mm Self Drilling Masonry Anchors with internal thread diameter from 6.00mm to 20mm Expansion Sleeve Anchors, Hex Nut, Flat Head, Round Head, Tie Wire, Setlock and made from heat treated, high tensile or mild steel with a diameter from 6.00mm to 20mm Heavy Duty Stud Anchors, made from mild or stainless steel in diameters 6.00mm to 24mm with an overall length from 45mm up to and including 250mm Drive Pins for power actuated tools with shank diameters from 2.00mm to 4.5mm with an overall length from 20mm up to and including 100mm Hardened Concrete Nails of shank diameters from 2.00mm to 4.5mm with an overall length from 15mm to 100mm		99	981949F	VA
Section XV	REQUESTED APPROVAL Plugs, clips and similar fittings peculiar to use by builders for fixing articles to concrete, plaster, plaster board etc EXCLUDING: Concrete Inserts stainless or mild steel with internal thread diameter 6.00mm to 24mm Self Drilling Masonry Anchors with internal thread diameter from 6.00mm to 20mm Expansion Sleeve Anchors, Hex Nut, Flat Head, Round Head, Tie Wire, Setlock and made from heat treated, high tensile or mild steel with a diameter from 6.00mm to 20mm Heavy Duty Stud Anchors, made from mild or stainless steel in diameters 6.00mm to 24mm with an overall length from 45mm up to and including 250mm Drive Pins for power actuated tools with shank diameters from 2.00mm to 4.5mm with an overall length from 20mm up to and including 100mm Hardened Concrete Nails of shank diameters from 2.00mm to 4.5mm with an overall length from 15mm to 100mm	Alan H Reid Engineering Ltd PO Box 60-112 Titirangi AUCKLAND 7	99	TCU 985543C	VA
+					
+					
+					
7307.29.11	Barbed pipe fittings in low sulphur content 300 series stainless steel	Crown Equipment Ltd C/- PO Box 2658 AUCKLAND 1	99	TCU 985485B	A
7308.30.00	Roll formed 115mm steel folding door panels	Won Door (NZ) Ltd C/- Source Customs Ltd PO Box 100-150 North Shore Mail Centre AUCKLAND	99	TCU 983127E	A
7326.90.09	Flame arresters of a type used for insertion into pipelines	Gas Services Ltd PO Box 3854 AUCKLAND 1	99	TCU 985482H	A
7326.90.09	Galvanised steel panel anchors being perforated 20 gauge strip 24' x 1 1/2"	George Forman & Sons Ltd PO Box 12149 Penrose AUCKLAND	99	TCU 984479B	A
7606.12.09	Coiled sheet, alloys 5005 and 5251, 0 temper, thickness 3.125mm, width 1260mm. Limited to 19 tonnes on IE 1210670115 shipment MV Prospect	Alcan New Zealand Ltd PO Box 308 WELLINGTON	99	TCU 985475E	A
7606.12.09	Coiled sheet as hot rolled, temper M, thickness 4.0mm, alloys 1200, 5005, 5251 and 5454, internal coil diameter,	Alcan New Zealand Ltd PO Box 308	99	TCU 985476C	WA